

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 6/9/2015 Revision date: 10/30/2018 Supersedes: 2/7/2018 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : BUILDING DECAPANT PEINTURE B
Product code : 304542

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

IPC SA
CS 71821 - 10, Quai Cdt Malbert 29218 BREST - France
T 02-98-43-45-44 - F 02-98-43-22-53 ipc@ipc-sa.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Flammable liquids, Category 2 H225
Skin corrosion/irritation, Category 1B H314
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. May cause respiratory irritation. Causes severe skin burns and eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger
Hazardous ingredients : 2-aminoethanol; 1-methoxypropane-2-ol
Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H314 - Causes severe skin burns and eye damage.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe dust, mist.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P310 - Immediately call a POISON CENTER, a doctor.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235 - Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No additional information available

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,3-dioxolane	(CAS-No.) 646-06-0 (EC-No.) 211-463-5 (EC Index-No.) 605-017-00-2 (REACH-no) 01-2119490744-29	40 - 60	Flam. Liq. 2, H225 Eye Irrit. 2, H319
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	10 - 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
1-methoxypropane-2-ol	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3 (REACH-no) 01-2119457435-35	10 - 25	Flam. Liq. 3, H226 STOT SE 3, H336
2-aminoethanol	(CAS-No.) 141-43-5 (EC-No.) 205-483-3 (EC Index-No.) 603-030-00-8 (REACH-no) 01-2119486455-28	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Chronic 3, H412
Ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	0 - 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	0 - 1	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT SE 1, H370
toluene substance with a Community workplace exposure limit	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	0 - 0.2	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336

Specific concentration limits:

Name	Product identifier	Specific concentration limits
2-aminoethanol	(CAS-No.) 141-43-5 (EC-No.) 205-483-3 (EC Index-No.) 603-030-00-8 (REACH-no) 01-2119486455-28	(C >= 5) STOT SE 3, H335
methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	(3 =<C < 10) STOT SE 2, H371 (C >= 10) STOT SE 1, H370

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Call a physician immediately.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact

: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Burns. Irritation.
- Symptoms/effects after eye contact : Eye irritation. Lacrimation. Serious damage to eyes.
- Symptoms/effects after ingestion : Abdominal pain, nausea. May cause irritation to the digestive tract. Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Hazardous decomposition products in case of fire : Carbon dioxide. fume. Carbon monoxide. May release flammable gases.

5.3. Advice for firefighters

- Precautionary measures fire : Stop leak if safe to do so. Evacuate area. Do not enter fire area without proper protective equipment, including respiratory protection. Eliminate all ignition sources if safe to do so. Keep cool. Protect from sunlight.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Do not get in eyes, on skin, or on clothing. Wear suitable gloves and eye/face protection.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust, mist, spray, fume, gas, vapours.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe spray, mist, fume, gas, dust, vapours.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in original container. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from freezing.
- Incompatible products : Strong acids. Strong bases. Oxidizing agent.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Maximum storage period : 13 months
Storage temperature : < 20 °C
Storage area : Store away from heat. Store in a well-ventilated place.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:					
Wear suitable gloves resistant to chemical penetration					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Polyvinylalcohol (PVA)				EN 374
Gloves	Nitrile rubber (NBR)				EN 374
Eye protection:					
Safety glasses. EN 166					
Skin and body protection:					
Wear suitable protective clothing					
Respiratory protection:					
In case of insufficient ventilation, wear suitable respiratory equipment					
Device	Filter type	Condition	Standard		
	Type A - High-boiling (>65 °C) organic compounds	In the event of insufficient ventilation:			

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Viscous liquid.
Colour : light yellow.
Odour : No data available
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : < 20 °C
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Not applicable
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : 1

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Solubility	: immiscible and insoluble.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. gel. Direct sunlight. Protect from sunlight.

10.5. Incompatible materials

Strong acids. Oxidizing agent. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1,3-dioxolane (646-06-0)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	68.4 mg/kg

methanol (67-56-1)

LD50 oral	5628 mg/kg bodyweight
LD50 dermal	15800 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	85000 mg/l

2-aminoethanol (141-43-5)

LD50 oral	1515 mg/kg bodyweight
LD50 dermal	2504 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	136 mg/l

Ethylbenzene (100-41-4)

LD50 oral	3500 mg/kg bodyweight
LD50 dermal	15350 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	17200 mg/l

xylene (1330-20-7)

LD50 oral	4300 mg/kg bodyweight
LD50 dermal	> 5000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 10000 mg/l

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-methoxypropane-2-ol (107-98-2)	
LD50 oral	3739 mg/kg bodyweight
LD50 dermal	> 2000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 26315 mg/l

toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 oral	5580 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg
LD50 dermal	12124 mg/kg bodyweight
LC50 inhalation rat (mg/l)	< 20 mg/l/4h
LC50 inhalation rat (Dust/Mist - mg/l/4h)	28100 mg/l

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Serious eye damage, category 1, implicit
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Do not discharge into drains or the environment. Before neutralisation, the product may represent a danger to aquatic organisms.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

1,3-dioxolane (646-06-0)	
LC50 fish 1	> 95.4 mg/l <i>Lepomis macrochirus</i>
EC50 Daphnia 1	772 mg/l <i>Daphnia magna</i>
EC50 72h algae (1)	877 mg/l <i>Selenastrum capricornutum</i>
NOEC chronic fish	546.3 mg/l
NOEC chronic crustacea	197.4 mg/l

methanol (67-56-1)	
LC50 fish 1	10800 mg/l
EC50 other aquatic organisms 1	10000 mg/l waterflea
EC50 other aquatic organisms 2	12000 mg/l
EC50 72h algae (1)	> 22000 mg/l <i>Pseudokichnerela subcapitata</i>

2-aminoethanol (141-43-5)	
LC50 fish 1	349 mg/l
EC50 other aquatic organisms 1	65 mg/l waterflea
EC50 other aquatic organisms 2	2.5 mg/l
EC50 72h algae (1)	2.8 mg/l <i>Pseudokirchneriella subcapitata</i>

Ethylbenzene (100-41-4)	
LC50 fish 1	12.1 mg/l

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 other aquatic organisms 1	2.2 mg/l waterflea
--------------------------------	--------------------

xylene (1330-20-7)

LC50 fish 1	> 86 mg/l
EC50 other aquatic organisms 1	350 mg/l waterflea

1-methoxypropane-2-ol (107-98-2)

LC50 fish 1	> 4600 mg/l
EC50 other aquatic organisms 1	23300 mg/l waterflea
EC50 other aquatic organisms 2	> 500 mg/l

toluene (108-88-3)

LC50 fish 1	5.5 mg/l
EC50 other aquatic organisms 1	3.78 mg/l waterflea

12.2. Persistence and degradability

1,3-dioxolane (646-06-0)

Persistence and degradability	The product is not biodegradable.
Biodegradation	3.7 % OCDE301D

2-aminoethanol (141-43-5)

Biodegradation	90 % 21 days
----------------	--------------

1-methoxypropane-2-ol (107-98-2)

Biodegradation	96 % 28 days OCDE301E
----------------	-----------------------

12.3. Bioaccumulative potential

1,3-dioxolane (646-06-0)

Log Pow	-0.37
---------	-------

methanol (67-56-1)

Log Pow	-0.7
---------	------

2-aminoethanol (141-43-5)

Log Pow	-1.31
---------	-------

Ethylbenzene (100-41-4)

Log Pow	3.6
---------	-----

xylene (1330-20-7)

Log Pow	3.1
---------	-----

1-methoxypropane-2-ol (107-98-2)

Log Pow	-0.49
---------	-------

toluene (108-88-3)

Log Pow	2.73
---------	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1993
UN-No. (IMDG) : 1993
UN-No. (IATA) : Not regulated
UN-No. (ADN) : Not regulated
UN-No. (RID) : Not regulated

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IATA) : Not regulated
Proper Shipping Name (ADN) : Not regulated
Proper Shipping Name (RID) : Not regulated
Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (1,3-dioxolane ; xylene ; 1-methoxypropane-2-ol), 3, II, (D/E)
Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : Not regulated

ADN

Transport hazard class(es) (ADN) : Not regulated

RID

Transport hazard class(es) (RID) : Not regulated

14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : Not regulated
Packing group (ADN) : Not regulated
Packing group (RID) : Not regulated

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

BUILDING DECAPANT PEINTURE B


Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640D
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28, TP8
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances
Directive 2012/18/EU (SEVESO III)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

BUILDING DECAPANT PEINTURE B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product