Version: N°1 (02/03/2022)

IPC

LOFT SYSTEM FIDJI

SAFETY DATA SHEET

Date: 29/04/2022 Page 1/11 Revision: N°1 (02/03/2022)

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: LOFT SYSTEM FIDJI

Product code: 107133

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

IPC

10, Quai MALBERT CS 71821 29218 BREST CEDEX 2 ipc@groupe-ipc.com Tel. +33 (0)2.98.43.45.44

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS02

GHS07

Signal Word:

DANGER

DANGER

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Precautionary statements - Storage:

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.

Revision: N°1 (02/03/2022)

Date: 29/04/2022 Page 2/11

LOFT SYSTEM FIDJI

Precautionary statements - Disposal:

P501 Eliminate the contents / container according to the local regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Identification	(EC) 1272/2008	Note	%
INDEX: 601_004_00_0	GHS02, GHS04	С	50 <= x % < 100
CAS: 106-97-8	Dgr	[1]	
EC: 203-448-7	Flam. Gas 1, H220	[7]	
REACH: 01-2119474691-32	Press. Gas, H280		
BUTANE			
INDEX: 601_003_00_5	GHS02, GHS04	[1]	10 <= x % < 25
CAS: 74-98-6	Dgr	[7]	
EC: 200-827-9	Flam. Gas 1, H220		
REACH: 01-2119486944-21	Press. Gas, H280		
PROPANE			
INDEX: 603_002_005A	GHS07, GHS02	[1]	10 <= x % < 25
CAS: 64-17-5	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43	Eye Irrit. 2, H319		
ETHANOL			
INDEX: 601_004_000A	GHS02, GHS04	C	$2.5 \ll x \% < 10$
CAS: 75-28-5	Dgr	[1]	
EC: 200-857-2	Flam. Gas 1, H220	[7]	
REACH: 01-2119485395-27	Press. Gas, H280		
AND ISOBUTANE			

Information on ingredients:

(Full text of H-phrases: see section 16)

- [7] Propellant gas
- [1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

Revision: N°1 (02/03/2022)

Date: 29/04/2022 Page 3/11

LOFT SYSTEM FIDJI

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Use some absorbent.

The elimination must be carried out by a registrated salvage professionnal.

Revision : N°1 (02/03/2022)

Date: 29/04/2022 Page 4/11

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

LOFT SYSTEM FIDJI

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

LOFT SYSTEM FIDJI

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

${\bf Occupational\ exposure\ limits:}$

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

Date: 29/04/2022 Page 5/11

Revision: N°1 (02/03/2022)

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
106-97-8	1000 ppm				
74-98-6	1000 ppm				
64-17-5		1000 ppm		A3	
75-28-5	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 08/08/2019):

CAS	VME :	VME:	Excess	Notes
106-97-8		1000 ppm		4(II)
		2400 mg/m ³		
74-98-6		1000 ppm		4(II)
		1800 mg/m ³		
64-17-5		200 ppm		4(II)
		380 mg/m^3		
75-28-5		1000 ppm		4(II)
		2400 mg/m ³		

- France (INRS - ED984 / 2020-1546):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
106-97-8	800	1900	-	-	-	-
64-17-5	1000	1900	5000	9500	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
106-97-8	600 ppm	750 ppm		Carc	
	1450 mg/m3	1810 mg/m3			
64-17-5	1000 ppm				
	1920 mg/m ³				

ETHANOL (CAS: 64-17-5)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 343 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects.

DNEL: 1900 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 950 mg of substance/m3

Final use: Man exposed via the environment.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 87 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

Revision: N°1 (02/03/2022)

Date: 29/04/2022 Page 6/11

LOFT SYSTEM FIDJI

DNEL: 206 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects. DNEL: 950 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 114 mg of substance/m3

Predicted no effect concentration (PNEC):

ETHANOL (CAS: 64-17-5)

Environmental compartment: Soil.

PNEC: 0.63 mg/kg

Environmental compartment: Fresh water. PNEC: 0.96 mg/l

Environmental compartment: Sea water. PNEC: 0.79 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 3.6 mg/kg

Environmental compartment: Marine sediment. PNEC: 2.9 mg/kg

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Version: N°1 (02/03/2022)

IPC

LOFT SYSTEM FIDJI

Date: 29/04/2022 Page 7/11 Revision: N°1 (02/03/2022)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES 9.1. Information on basic physical and chemical properties Physical state Physical state: Fluid liquid. Colour Unspecified Odour Not stated. Odour threshold: **Melting point** Melting point/melting range: Not specified. Freezing point Not stated. Freezing point / Freezing range: Boiling point or initial boiling point and boiling range Boiling point/boiling range: Not specified. **Flammability** Flammability (solid, gas): Not stated. Lower and upper explosion limit Not stated. Explosive properties, lower explosivity limit (%): Not stated. Explosive properties, upper explosivity limit (%): Flash point Flash point interval: Not relevant **Auto-ignition temperature** Self-ignition temperature: Not specified. **Decomposition temperature** Not relevant. Decomposition point/decomposition range: pН Not stated. pH: pH (aqueous solution): Not stated. Kinematic viscosity Not stated. Viscosity: **Solubility** Water solubility: Insoluble. Fat solubility: Not stated. Partition coefficient n-octanol/water (log value) Partition coefficient: n-octanol/water: Not stated. Vapour pressure Vapour pressure (50°C): Below 110 kPa (1.10 bar). Density and/or relative density < 1 Density: Relative vapour density Vapour density: Not stated. 9.2. Other information No data available.

Not specified. Deflagration density: Not specified.

9.2.1. Information with regard to physical hazard classes

No data available.

Inflammation time:

Chemical combustion heat:

Aerosols

Not specified.

Version: N°1 (02/03/2022)

IPC

LOFT SYSTEM FIDJI

Inflammation distance :Not specified.Flame height :Not specified.Flame duration :Not specified.

9.2.2. Other safety characteristics

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

Date: 29/04/2022 Page 8/11 Revision: N°1 (02/03/2022)

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- heating
- heat

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Serious damage to eyes/eye irritation:

ETHANOL (CAS: 64-17-5)

Causes serious eye irritation.

Corneal haze : $1 \le \text{Average score} \le 2$ and effects totally reversible within 21 days of observation

Conjunctival redness: $2 \le \text{Average score} < 2.5$ and effects totally reversible within 21 days of observation

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards

$Monograph(s)\ from\ the\ IARC\ (International\ Agency\ for\ Research\ on\ Cancer):$

CAS 64-17-5: IARC Group 1: The agent is carcinogenic to humans.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

Version: N°1 (02/03/2022)

IPC

Revision: N°1 (02/03/2022)

Date: 29/04/2022 Page 9/11

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

LOFT SYSTEM FIDJI

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification:



14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344	E0	2	D
							625			

Version: N°1 (02/03/2022)

IPC

LOFT SYSTEM FIDJI

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregation
								Handling	
	2	See SP63	-	See SP277	F-D. S-U	63 190 277	E0	- SW1 SW22	SG69
						327 344 381			
						959			

Date: 29/04/2022 Page 10/11

Revision: N°1 (02/03/2022)

	IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
		2.1	-	-	203	75 kg	203	150 kg	A145 A167	E0
									A802	
ſ		2.1	-	-	Y203	30 kg G	-	-	A145 A167	E0
									A802	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

Abbreviations:

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

STEL: Short-term exposure limit TWA: Time Weighted Averages

TMP: French Occupational Illness table TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

Version: N°1 (02/03/2022)

IPC

LOFT SYSTEM FIDJI

Date: 29/04/2022 Page 11/11 Revision: N°1 (02/03/2022)

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods. IATA : International Air Transport Association. ICAO : International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02: Flame

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.