Date: 18/10/2022 Page 1/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

# **SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

# SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: LOFT SYSTEM OCEAN INDIEN

Product code: 107250

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

10 Quai Malbert, 29200, BREST, FRANCE.

Tel.: +33 (0)2 98 43 45 44. Fax: +33 (0)2 98 44 22 53

ipc@groupe-ipc.com

# 1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

May produce an allergic reaction (EUH208).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

The propellant gas is taken into account when determining the health and environmental classification of the mixture.

# 2.2. Label elements

Mixture for aerosol application.

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS02 GHS07

Signal Word:

**DANGER** 

Additional labeling:

**EUH208** Contains PIPERONAL. May produce an allergic reaction. **EUH208** Contains DL-LIMONENE. May produce an allergic reaction.

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Date: 18/10/2022 Page 2/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Precautionary statements - Storage:

P410 + P412Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.

# 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

**Composition:** 

Identification	(EC) 1272/2008	Note	%
INDEX: 601_004_00_0	GHS02, GHS04	C	50 <= x % < 100
CAS: 106-97-8	Dgr	[1]	30 <- X % < 100
EC: 203-448-7	Flam. Gas 1, H220		
REACH: 01-2119474691-32	Press. Gas, H280	[7]	
REACH: 01-21194/4091-32	Press. Gas, H280		
BUTANE			
INDEX: 603_002_005A	GHS07, GHS02	[1]	10 <= x % < 25
CAS: 64-17-5		[1]	10 <= X % < 23
1	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43	Eye Irrit. 2, H319		
ETHANOL			
INDEX: 601_003_00_5	GHS02, GHS04	[1]	10 <= x % < 25
CAS: 74-98-6	Dgr	[7]	
EC: 200-827-9	Flam. Gas 1, H220		
REACH: 01-2119486944-21	Press. Gas, H280		
	,		
PROPANE			
INDEX: 601_004_000A	GHS02, GHS04	С	2.5 <= x % < 10
CAS: 75-28-5	Dgr	[1]	
EC: 200-857-2	Flam. Gas 1, H220	[7]	
REACH: 01-2119485395-27	Press. Gas, H280		
	,		
AND ISOBUTANE			
INDEX: B120570	GHS07, GHS08	[2]	0 <= x % < 1
CAS: 120-57-0	Wng		
EC: 204-409-7	Skin Sens. 1B, H317		
REACH: 01-2119983608-21	Repr. 2, H361		
PIPERONAL			
INDEX: I601029007	GHS02, GHS07, GHS08, GHS09		0 <= x % < 1
CAS: 138-86-3	Dgr		
EC: 205-341-0	Flam. Liq. 3, H226		
	Asp. Tox. 1, H304		
DL-LIMONENE	Skin Irrit. 2, H315		
	Skin Sens. 1B, H317		
	Aquatic Chronic 3, H412		
	Aquatic Acute 1, H400		
	M Acute = 1		
	1.110410 - 1		

Date: 18/10/2022 Page 3/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

#### **Information on ingredients:**

(Full text of H-phrases: see section 16)

- [1] Substance for which maximum workplace exposure limits are available.
- [2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.
- [7] Propellant gas

#### **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. description of first aid measures

# In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

#### In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

# In the event of splashes or contact with skin:

In the event of an allergic reaction, seek medical attention.

## In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# **SECTION 5: FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

# 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

# Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

## Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)

Date: 18/10/2022 Page 4/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

## For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

# 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

The elimination must be carried out by a registrated salvage professionnal.

#### 6.4. Reference to other sections

No data available.

#### **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

#### Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

## Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Date: 18/10/2022 Page 5/11 Revision: N°10 (18/10/2022) Version: N°1 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

# Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.

# Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Always keep in packaging made of an identical material to the original.

# 7.3. Specific end use(s)

No data available.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

#### Occupational exposure limits:

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
106-97-8	1000 ppm				
64-17-5		1000 ppm		A3	
74-98-6	1000 ppm				
75-28-5	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME:	VME:	Excess	Notes
106-97-8		1000 ppm		4(II)
		2400 mg/m <sup>3</sup>		
64-17-5		200 ppm		4(II)
		380 mg/m <sup>3</sup>		
74-98-6		1000 ppm		4(II)
		1800 mg/m <sup>3</sup>		
75-28-5		1000 ppm		4(II)
		2400 mg/m <sup>3</sup>		

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
106-97-8	800	1900	-	-	-	-
64-17-5	1000	1900	5000	9500	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
106-97-8	600 ppm	750 ppm		Carc	
	1450 mg/m3	1810 mg/m3			
64-17-5	1000 ppm				
	1920 mg/m <sup>3</sup>				

# Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ETHANOL (CAS: 64-17-5)

Final use: Workers. Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

Date: 18/10/2022 Page 6/11 Revision: N°10 (18/10/2022) Version: N°1 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

DNEL: 343 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects. DNEL: 1900 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects. DNEL: 950 mg of substance/m3

Final use: Man exposed via the environment.

Exposure method: Ingestion.

Long term systemic effects. Potential health effects: DNEL: 87 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects. DNEL: 206 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects. DNEL: 950 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects. DNEL: 114 mg of substance/m3

# Predicted no effect concentration (PNEC):

ETHANOL (CAS: 64-17-5)

Environmental compartment: Soil.

PNEC: 0.63 mg/kg

Environmental compartment: Fresh water. PNEC: 0.96 mg/l Environmental compartment: Sea water.

PNEC: 0.79 mg/l

Fresh water sediment. Environmental compartment:

PNEC: 3.6 mg/kg

Environmental compartment: Marine sediment. PNEC: 2.9 mg/kg

# 8.2. Exposure controls

# Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

# - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

Date: 18/10/2022 Page 7/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES** 9.1. Information on basic physical and chemical properties

Physical state	
Physical state:	Fluid liquid.

Colour Unspecified

Odour

Odour threshold: Not stated.

Melting point

Melting point/melting range: Not specified.

Freezing point

Freezing point / Freezing range: Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range: Not specified.

**Flammability** 

Not stated. Flammability (solid, gas):

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%): Not stated. Not stated. Explosive properties, upper explosivity limit (%):

Flash point

Flash point interval: Not relevant.

Auto-ignition temperature

Self-ignition temperature: Not specified.

**Decomposition temperature** 

Decomposition point/decomposition range: Not specified.

pН

pH: Not relevant. Not stated. pH (aqueous solution):

Kinematic viscosity

Viscosity: Not stated.

Viscosity:  $v < 7 \text{ mm}2/s (40^{\circ}\text{C})$ 

**Solubility** 

Water solubility: Dilutable.

Date: 18/10/2022 Page 8/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

Fat solubility: Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Not relevant.

Density and/or relative density

Density: < 1

Relative vapour density

Not stated. Vapour density:

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

Aerosols

Chemical combustion heat: >= 30 kJ/g.

9.2.2. Other safety characteristics

No data available.

#### **SECTION 10: STABILITY AND REACTIVITY**

# 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- heating
- heat
- accumulation of electrostatic charges.
- flames and hot surfaces

# 10.5. Incompatible materials

Keep away from:

- strong oxidising agents

# 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

# SECTION 11: TOXICOLOGICAL INFORMATION

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

# 11.1.1. Substances

# Serious damage to eyes/eye irritation:

ETHANOL (CAS: 64-17-5)

Causes serious eye irritation.

Date: 18/10/2022 Page 9/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

Corneal haze: 1 <= Average score < 2 and effects totally reversible within 21 days of observation

Conjunctival redness: 2 <= Average score < 2.5 and effects totally reversible within 21 days of observation

#### 11.1.2. Mixture

#### Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

#### 11.2. Information on other hazards

#### Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 123-35-3: IARC Group 2B: The agent is possibly carcinogenic to humans.

CAS 91-64-5: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

CAS 102-71-6: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

CAS 64-17-5: IARC Group 1: The agent is carcinogenic to humans.

#### **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

#### **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

# 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

No data available.

## 12.6. Endocrine disrupting properties

No data available

# 12.7. Other adverse effects

# SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

# 13.1. Waste treatment methods

Do not pour into drains or waterways.

### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

## Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

### 14.1. UN number or ID number

# 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

Date: 18/10/2022 Page 10/11 Version: N°1 (18/10/2022) Revision: N°10 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

# 14.3. Transport hazard class(es)

- Classification:



2.1

# 14.4. Packing group

# 14.5. Environmental hazards

# 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344	E0	2	D
							625			

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregation
								Handling	
	2	See SP63	-	See SP277	F-D. S-U	63 190 277	E0	- SW1 SW22	SG69
						327 344 381			
						959			

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167	E0
								A802	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167	E0
								A802	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

# 14.7. Maritime transport in bulk according to IMO instruments

No data available.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

## - Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

# - Particular provisions :

No data available.

#### 15.2. Chemical safety assessment

No data available.

Date: 18/10/2022 Page 11/11 Revision: N°10 (18/10/2022) Version: N°1 (18/10/2022)

# LOFT SYSTEM OCEAN INDIEN

#### **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section 3:

wording of the phrases ment	ioneu in section 3.
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child .
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

# **Abbreviations:**

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration CMR: Carcinogenic, mutagenic or reprotoxic.

UFI: Unique formulation identifier. STEL: Short-term exposure limit TWA: Time Weighted Averages TMP: French Occupational Illness table

TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02: Flame

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.