### LOFT SYSTEM ROMANCE

Date: 10/04/2024 Page 1/13 Revision: N°5 (10/04/2024)

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name: LOFT SYSTEM ROMANCE

Product code: 108680

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Deodorant

# 1.3. Details of the supplier of the safety data sheet

Registered company name: IPC

10 Quai Malbert, 29200, BREST, FRANCE.

Tel.: +33 (0)2 98 43 45 44. Fax: +33 (0)2 98 44 22 53

ipc@groupe-ipc.com

# 1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

### Other emergency numbers

Une liste des numéros d'appels d'urgence pour l'ensemble des pays de l'Union Européenne est disponible sur le site internet de l'Echa (https://echa.europa.eu/fr/support/helpdesks)

A list of emergency telephone numbers for all European Union countries is available on the Echa website

(https://echa.europa.eu/fr/support/helpdesks)

# **SECTION 2: HAZARDS IDENTIFICATION**

# 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

May produce an allergic reaction (EUH208).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

The propellant gas is taken into account when determining the health and environmental classification of the mixture.

### 2.2. Label elements

Mixture for aerosol application.

## In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS02

Signal Word: DANGER

Additional labeling:

Contains 1-(1,2,3,4,5,6,7,8-OCTAHYDRO-2,3,8,8-TETRAMETHYL-2-NAPHTHALENYL)ETHANONE. **EUH208** 

May produce an allergic reaction.

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

### LOFT SYSTEM ROMANCE

Precautionary statements - Storage:

P410 + P412Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

Other information:

Do not spray for a long time.

Use and keep only in well ventilated zones. Do not use for a usage other one than the one for which

Date: 10/04/2024 Page 2/13 Revision: N°5 (10/04/2024)

the product is intended.

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 59 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

(EC) 1272/2000

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

**Composition:** 

| Identification                          | Classification (EC) 1272/2008 | Note  | %                    |
|---|-------------------------------|-------|----------------------|
| INDEX: 601-004-00-0                     | GHS02, GHS04                  | С     | 25 <= x % < 50       |
| CAS: 106-97-8                           | Dgr                           | [i]   |                      |
| EC: 203-448-7                           | Flam. Gas 1A, H220            | [vii] |                      |
| BUTANE                                  |                               |       |                      |
| CAS: 64-17-5                            | GHS07, GHS02                  | [i]   | 25 <= x % < 50       |
| EC: 200-578-6                           | Dgr                           |       |                      |
| REACH: 01-2119457610-43                 | Flam. Liq. 2, H225            |       |                      |
| EMILANOI                                | Eye Irrit. 2, H319            |       |                      |
| ETHANOL                                 | GHG02 GHG04                   |       | 10                   |
| INDEX: 601-004-00-0                     | GHS02, GHS04                  | C     | $10 \le x \% \le 25$ |
| CAS: 75-28-5                            | Dgr                           | [i]   |                      |
| EC: 200-857-2                           | Flam. Gas 1A, H220            | [vii] |                      |
| AND ISOBUTANE                           |                               |       |                      |
| INDEX: 601-003-00-5                     | GHS02, GHS04                  | [i]   | 2.5 <= x % < 10      |
| CAS: 74-98-6                            | Dgr                           | [vii] |                      |
| EC: 200-827-9                           | Flam. Gas 1A, H220            |       |                      |
| PROPANE                                 |                               |       |                      |
| CAS: 25265-71-8                         |                               | [i]   | 2.5 <= x % < 10      |
| EC: 246-770-3                           |                               |       |                      |
| REACH: 01-2119456811-38                 |                               |       |                      |
| DIPROPYLENE GLYCOL                      |                               |       |                      |
| CAS: 68439-50-9                         | GHS07, GHS09                  |       | 0 <= x % < 2.5       |
| EC: 500-213-3                           | Wng                           |       | 0 1- 1 70 1 2.3      |
| EC. 300 213 3                           | Eye Irrit. 2, H319            |       |                      |
| ALCOHOLS C12-14, ETHOXYLATED            | Aquatic Chronic 3, H412       |       |                      |
| ,                                       | Aquatic Acute 1, H400         |       |                      |
|   | M Acute = 1                   |       |                      |
| CAS: 54464-57-2                         | GHS07, GHS09                  |       | 0 <= x % < 2.5       |
| EC: 259-174-3                           | Wng                           |       |                      |
|   | Skin Irrit. 2, H315           |       |                      |
| 1-(1,2,3,4,5,6,7,8-OCTAHYDRO-2,3,8,8-TE | ,                             |       |                      |
| AMETHYL-2-NAPHTHALENYL)ETHANG           |                               |       |                      |
|   | M Chronic = 1                 |       |                      |

# **Specific concentration limits:**

| Identification          | Specific concentration limits | ATE |  |
|-------------------------|-------------------------------|-----|--|
| CAS: 64-17-5            | Eye Irrit. 2: H319 C>= 50%    |     |  |
| EC: 200-578-6           |                               |     |  |
| REACH: 01-2119457610-43 |                               |     |  |
|                         |                               |     |  |
| ETHANOL                 |                               |     |  |

# Information on ingredients:

(Full text of H-phrases: see section 16)

Date: 10/04/2024 Page 3/13 Revision: N°5 (10/04/2024) Version: N°1 (10/04/2024)

#### LOFT SYSTEM ROMANCE

Substances may not have a REACH Registration No.. because they are manufactured / imported in quantities less than 1 ton / year, or they are complex substances or they are exempted from registration under REACH.

[i] Substance for which maximum workplace exposure limits are available.

[vii] Propellant gas

### **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. description of first aid measures

### In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

In case of massive inhalation transport the patient outdoors and keep him for the warmth and for the rest.

Consult doctor if symptoms develop.

### In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Consult a doctor with the label.

### In the event of splashes or contact with skin:

In the event of an allergic reaction, seek medical attention.

Lave bem a pele com água. Se a irritação persistir, chame um médico.

### In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

# **Specific and immediate treatment:**

No data available.

# Information for the doctor:

No data available.

# **SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

# 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

# Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

## Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

### LOFT SYSTEM ROMANCE

Date: 10/04/2024 Page 4/13 Revision: N°5 (10/04/2024)

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

See Section 7 for information on safe handling.

### **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

### Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

## Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

# Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

Date: 10/04/2024 Page 5/13 Revision: N°5 (10/04/2024) Version: N°1 (10/04/2024)

## LOFT SYSTEM ROMANCE

# Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

## **Packaging**

Always keep in packaging made of an identical material to the original.

## 7.3. Specific end use(s)

No data available.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## **8.1.** Control parameters

# Occupational exposure limits:

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

| CAS      | TWA:     | STEL:    | Ceiling : | Definition: | Criteria: |
|----------|----------|----------|-----------|-------------|-----------|
| 106-97-8 | 1000 ppm |          |           |             |           |
| 64-17-5  |          | 1000 ppm |           | A3          |           |
| 75-28-5  | 1000 ppm |          |           |             |           |
| 74-98-6  | 1000 ppm |          |           |             |           |

# - Germany - AGW (BAuA - TRGS 900, 02/2022) :

| CAS        | VME: | VME:        | Excess | Notes |
|------------|------|-------------|--------|-------|
| 106-97-8   |      | 1000 ppm    |        | 4(II) |
|            |      | 2400 mg/m3  |        |       |
| 64-17-5    |      | 200 ppm     |        | 4(II) |
|            |      | 380 mg/m3   |        |       |
| 75-28-5    |      | 1000 ppm    |        | 4(II) |
|            |      | 2400 mg/m3  |        |       |
| 74-98-6    |      | 1000 ppm    |        | 4(II) |
|            |      | 1800 mg/m3  |        |       |
| 25265-71-8 |      | 100 E mg/m3 |        | 2(II) |

# - Belgium (Royal decree of 11/05/2021):

| CAS      | TWA:       | STEL:      | Ceiling: | Definition: | Criteria: |
|----------|------------|------------|----------|-------------|-----------|
| 106-97-8 |            | 980 ppm    |          |             |           |
|          |            | 2370 mg/m3 |          |             |           |
| 64-17-5  | 1000 ppm   |            |          |             |           |
|          | 1907 mg/m3 |            |          |             |           |
| 75-28-5  |            | 980 ppm    |          |             |           |
|          |            | 2370 mg/m3 |          |             |           |
| 74-98-6  | 1000 ppm   |            |          |             |           |

# - France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

| CAS      | VME-ppm: | VME-mg/m3: | VLE-ppm: | VLE-mg/m3: | Notes: | TMP No: |
|----------|----------|------------|----------|------------|--------|---------|
| 106-97-8 | 800      | 1900       |          |            |        |         |
| 64-17-5  | 1000     | 1900       | 5000     | 9500       |        | 84      |

- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2019) :

| CAS      | TWA:       | STEL:               | Ceiling: | Definition: | Criteria: |
|----------|------------|---------------------|----------|-------------|-----------|
| 106-97-8 | 1. 000 ppm |                     |          |             |           |
| 64-17-5  |            | 1 ppm<br>1.91 mg/m3 |          | S           |           |
| 74-98-6  | 1. 000 ppm |                     |          |             |           |

## - Switzerland (Suva 2021):

| ĺ | CAS      | VME        | VLE        | Valeur plafond | Notations |
|---|----------|------------|------------|----------------|-----------|
| I | 106-97-8 | 800 ppm    | 3200 ppm   |                |           |
| ı |          | 1900 mg/m3 | 7600 mg/m3 |                |           |
| ĺ | 64-17-5  | 500 ppm    | 1000 ppm   |                | SSC       |
| ı |          |            | 1920 mg/m3 |                |           |

### LOFT SYSTEM ROMANCE

Date: 10/04/2024 Page 6/13 Revision: N°5 (10/04/2024)

| 75-28-5    | 800 ppm    | 3200 ppm   |     |
|------------|------------|------------|-----|
|            | 1900 mg/m3 | 7600 mg/m3 |     |
| 74-98-6    | 1000 ppm   | 4000 ppm   |     |
|            | 1800 mg/m3 | 7200 mg/m3 |     |
| 25265-71-8 | 140 mg/m3  | 280 mg/m3  | SSC |

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

| CAS      | TWA:       | STEL:      | Ceiling: | Definition: | Criteria: |
|----------|------------|------------|----------|-------------|-----------|
| 106-97-8 | 600 ppm    | 750 ppm    |          | Carc        |           |
|          | 1450 mg/m3 | 1810 mg/m3 |          |             |           |
| 64-17-5  | 1000 ppm   |            |          |             |           |
|          | 1920 mg/m3 |            |          |             |           |

# Derived no effect level (DNEL) or derived minimum effect level (DMEL):

DIPROPYLENE GLYCOL (CAS: 25265-71-8)

**Final use:**Exposure method:
Workers.
Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 84 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects. DNEL: 238 mg of substance/m3

Final use: Consumers. Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 24 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 51 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 70 mg of substance/m3

ETHANOL (CAS: 64-17-5)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 343 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.
DNEL: 950 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 87 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 206 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 114 mg of substance/m3

Date: 10/04/2024 Page 7/13 Revision: N°5 (10/04/2024)

Predicted no effect concentration (PNEC):

DIPROPYLENE GLYCOL (CAS: 25265-71-8)

Environmental compartment: Soil.
PNEC: 0.025 mg/kg

Environmental compartment: Fresh water. PNEC: 0.1 mg/l

Environmental compartment: Sea water. PNEC: 0.01 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 1 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 0.238 mg/kg

Environmental compartment: Marine sediment. PNEC: 0.024 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 1000 mg/l

Environmental compartment: Vermivore predators (oral).

PNEC: 313 mg/kg

ETHANOL (CAS: 64-17-5)

Environmental compartment: Soil.
PNEC: 0.63 mg/kg

Environmental compartment: Fresh water. PNEC: 0.96 mg/l

Environmental compartment: Sea water. PNEC: 0.79 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 2.75 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 3.6 mg/kg

Environmental compartment: Marine sediment. PNEC: 2.9 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 580 mg/l

Environmental compartment: Vermivore predators (oral).

PNEC: 0.38 mg/kg

# 8.2. Exposure controls

# Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

### LOFT SYSTEM ROMANCE

Date: 10/04/2024 Page 8/13 Revision: N°5 (10/04/2024)

### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

Let the glove manufacturer advise you on the choice of gloves and their duration of use for your operating conditions

### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

### - Respiratory protection

Category:

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

Particle filter according to standard EN143:

Types, classes and filters for respiratory protection above are recommended in case of confrontation at concentrations higher than the exposure limits specified under 8.1. (Control parameters) .They should be adjusted according to actual conditions. they may not be necessary if the product is used outdoors or in a well ventilated area.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical state

Physical state: Fluid liquid.

Spray.

Colour

Unspecified

Odour

Odour threshold: Not stated.

Melting point

Melting point/melting range: Not specified.

Freezing point

Not stated. Freezing point / Freezing range:

Boiling point or initial boiling point and boiling range

Not specified. Boiling point/boiling range:

**Flammability** 

Flammability (solid, gas): Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.

Explosive properties, upper explosivity limit (%) Not stated.

Flash point

Flash point interval: Not relevant.

**Auto-ignition temperature** 

Self-ignition temperature: Not specified.

**Decomposition temperature** 

Decomposition point/decomposition range: Not specified.

## LOFT SYSTEM ROMANCE

Date: 10/04/2024 Page 9/13 Revision: N°5 (10/04/2024)

pН

Not relevant. Not stated. pH (aqueous solution):

Kinematic viscosity

Not stated. Viscosity:

 $v < 7 \text{ mm}2/s (40^{\circ}\text{C})$ Viscosity:

**Solubility** 

Water solubility: Insoluble. Fat solubility: Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Not relevant.

Density and/or relative density

< 1 Density:

Relative vapour density

Vapour density: Not stated.

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

602.9 VOC(g/l):

9.2.1. Information with regard to physical hazard classes

No data available.

Aerosols

Chemical combustion heat: Not specified. Inflammation time: Not specified. Deflagration density: Not specified. Inflammation distance: Not specified. Flame height: Not specified. Not specified. Flame duration:

9.2.2. Other safety characteristics

No data available.

## **SECTION 10: STABILITY AND REACTIVITY**

# 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

# 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- heating
- heat

## 10.5. Incompatible materials

No data available.

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

Date: 10/04/2024 Page 10/13 Revision: N°5 (10/04/2024)

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

#### 11.1.1. Substances

# Acute toxicity:

ETHANOL (CAS: 64-17-5)

Oral route : LD50 > 5000 mg/kg bodyweight/day

Species: Rat

Inhalation route (Vapours) : LC50 > 1000 mg/l

Species: Mouse

### 11.1.2. Mixture

#### Skin corrosion/skin irritation:

Based on available data; the classification criteria are not met.

### Serious damage to eyes/eye irritation:

Based on available data the classification criteria are not met.

## Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

To be translated (XML)

## Germ cell mutagenicity:

Based on available data; the classification criteria are not met.

# **Carcinogenicity:**

Based on available data; the classification criteria are not met.

## **Reproductive toxicant:**

Based on available data; the classification criteria are not met.

# Specific target organ systemic toxicity - single exposure :

Based on available data; the classification criteria are not met.

# Specific target organ systemic toxicity - repeated exposure :

Based on available data; the classification criteria are not met.

# Aspiration hazard :

Based on available data; the classification criteria are not met.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

No further relevant information available.

# 11.2. Information on other hazards

# **Endocrine disrupting properties**

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

## Other information

No further relevant information available.

# **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

# 12.1.1. Substances

ETHANOL (CAS: 64-17-5)

Fish toxicity: LC50 > 100 mg/l

Crustacean toxicity: EC50 > 100 mg/l

## LOFT SYSTEM ROMANCE

Date: 10/04/2024 Page 11/13 Revision: N°5 (10/04/2024)

ECr50 > 100 mg/lAlgae toxicity:

Aquatic plant toxicity: ECr50 > 100 mg/l

### **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

## 12.2. Persistence and degradability

#### 12.2.1. Substances

ALCOHOLS C12-14, ETHOXYLATED (CAS: 68439-50-9)

Biodegradability: Rapidly degradable.

ETHANOL (CAS: 64-17-5)

Biodegradability: Rapidly degradable.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

No data available.

## 12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

### 12.7. Other adverse effects

No data available.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

# 13.1. Waste treatment methods

Do not pour into drains or waterways.

# Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

# Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2024 [65]).

### 14.1. UN number or ID number

1950

# 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

# 14.3. Transport hazard class(es)

- Classification:



2.1

# 14.4. Packing group

Date: 10/04/2024 Page 12/13

Revision: N°5 (10/04/2024)

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

| ADR/RID | Class | Code | Pack gr. | Label | Ident. | LQ  | Provis.     | EQ | Cat. | Tunnel |
|---------|-------|------|----------|-------|--------|-----|-------------|----|------|--------|
|         | 2     | 5F   | -        | 2.1   | -      | 1 L | 190 327 344 | E0 | 2    | D      |
|         |       |      |          |       |        |     | 625         |    |      |        |

| I | MDG | Class | 2°Label  | Pack gr. | LQ        | EMS      | Provis.     | EQ | Stowage    | Segregation |
|---|-----|-------|----------|----------|-----------|----------|-------------|----|------------|-------------|
|   |     |       |          |          |           |          |             |    | Handling   |             |
|   |     | 2     | See SP63 | -        | See SP277 | F-D. S-U | 63 190 277  | E0 | - SW1 SW22 | SG69        |
|   |     |       |          |          |           |          | 327 344 381 |    |            |             |
|   |     |       |          |          |           |          | 959         |    |            |             |

| IATA | Class | 2°Label | Pack gr. | Passager | Passager | Cargo | Cargo  | note      | EQ |
|------|-------|---------|----------|----------|----------|-------|--------|-----------|----|
|      | 2.1   | -       | -        | 203      | 75 kg    | 203   | 150 kg | A145 A167 | E0 |
|      |       |         |          |          |          |       |        | A802      |    |
|      | 2.1   | -       | -        | Y203     | 30 kg G  | -     | -      | A145 A167 | E0 |
|      |       |         |          |          |          |       |        | A802      |    |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

## 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/197. (ATP 21)

### **Container information:**

No data available.

### Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

# **Explosives precursors:**

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

# Particular provisions:

No data available.

# 15.2. Chemical safety assessment

The chemical safety assessment has not been carried out for this mixture.

# **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section 3:

| H220 | Extremely flammable gas.                              |
|------|---|
| H225 | Highly flammable liquid and vapour.                   |
| H315 | Causes skin irritation.                               |
| H317 | May cause an allergic skin reaction.                  |
| H319 | Causes serious eye irritation.                        |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects.    |

Date: 10/04/2024 Page 13/13 Revision: N°5 (10/04/2024)

# Abbreviations and acronyms:

LD50: The dose of a test substance resulting in 50% lethality in a given time period.

LC50: The concentration of a test substance resulting in 50% lethality in a given period.

EC50: The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

 $UFI: Unique\ formulation\ identifier.$ 

STEL: Short-term exposure limit

TWA: Time Weighted Averages

TMP: French Occupational Illness table TLV: Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

 $IMDG: International\ Maritime\ Dangerous\ Goods.$ 

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02: Flame

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.