

METALUSTRE

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : METALUSTRE

Product code : 10860

1.2. Relevant identified uses of the substance or mixture and uses advised against

Detergent.

Professional use.

1.3. Details of the supplier of the safety data sheet

Registered company name : IPC.

Address : 10 Quai Malbert.29200.BREST.FRANCE.

Telephone : +33 (0)2 98 43 45 44. Fax : .

ipc@ipc-sa.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

Mixture for spray application.

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07



GHS02

Signal Word :

DANGER

Hazard statements :

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist/vapours.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**METALUSTRE**

**Precautionary statements - Response :**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

**Precautionary statements - Storage :**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Spray by brief pressure

For safety, use only for the intended purpose and in accordance with the instructions for use.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

| Identification   | (EC) 1272/2008   | Note            | %               |
|--|--|-----------------|-----------------|
| INDEX: 1344_28_1<br>CAS: 1344-28-1<br>EC: 215-691-6<br>REACH: 01-2119529248-35<br><br>ALUMINUM OXIDE                     |  | [1]             | 10 <= x % < 25  |
| INDEX: 920_901_0<br>EC: 920-901-0<br>REACH: 01-2119456810-40<br><br>HYDROCARBONS, C11-C13, ISOALKANES,<br>< 2% AROMATICS | GHS08<br>Dgr<br>Asp. Tox. 1, H304<br>EUH:066   |                 | 10 <= x % < 25  |
| INDEX: 601_004_00_0<br>CAS: 106-97-8<br>EC: 203-448-7<br>REACH: 01-2119474691-32<br><br>BUTANE                           | GHS02<br>Dgr<br>Flam. Gas 1, H220<br>Press. Gas, H280  | C<br>[1]<br>[7] | 2.5 <= x % < 10 |
| INDEX: 603_030_00_8<br>CAS: 141-43-5<br>EC: 205-483-3<br>REACH: 01-2119486455-28<br><br>2-AMINOETHANOL                   | GHS07, GHS05<br>Dgr<br>Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1B, H314<br>Acute Tox. 4, H332<br>STOT SE 3, H335<br>Aquatic Chronic 3, H412 | [1]             | 2.5 <= x % < 10 |

**Information on ingredients :**

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person to fresh air and keep warm and at rest.

If the person is unconscious, place the person in a lateral safety position. Inform a doctor in all cases to judge the opportunity for monitoring and symptomatic treatment in hospital.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

---

**METALUSTRE**

---

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

In case of accidental spills, pay attention to slippery surfaces and floors.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

## METALUSTRE

---

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

---

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Ensure adequate ventilation.

Avoid all contact with skin and eyes.

Avoid the accumulation of electrostatic loads.

Follow the rules of hygiene and safety with regard to flammability.

No smoking.

Do not breathe vapors.

### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Keep away from ignition sources.

VAPORS MAY BE HARMFUL IN CASE OF COMBUSTION.

Keep away from electrical equipment while operating.

### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Use of safety goggles and gloves recommended.

Keep in original packaging. Do not pierce or burn even after use.

Storage and handling instructions for pressurized gases

### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

**METALUSTRE**

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Recommended storage temperature: + 5°C to + 40°C

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

| CAS      | VME-mg/m3 : | VME-ppm : | VLE-mg/m3 : | VLE-ppm : | Notes : |
|----------|-------------|-----------|-------------|-----------|---------|
| 141-43-5 | 2.5         | 1         | 7.6         | 3         | Peau    |

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

| CAS       | TWA :    | STEL : | Ceiling : | Definition : | Criteria : |
|-----------|----------|--------|-----------|--------------|------------|
| 1344-28-1 | 10 mg/m3 | -      | -         | -            | -          |
| 106-97-8  | 1000 ppm |        |           |              |            |
| 141-43-5  | 3 ppm    | 6 ppm  |           |              |            |

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

| CAS      | VME : | VME :                  | Excess | Notes |
|----------|-------|------------------------|--------|-------|
| 106-97-8 |       | 1000 ppm<br>2400 mg/m3 |        | 4(II) |
| 141-43-5 |       | 2 ppm<br>5,1 mg/m3     |        | 2(I)  |

- France (INRS - ED984 :2012) :

| CAS       | VME-ppm : | VME-mg/m3 : | VLE-ppm : | VLE-mg/m3 : | Notes : | TMP No :   |
|-----------|-----------|-------------|-----------|-------------|---------|------------|
| 1344-28-1 | -         | 10          | -         | -           | -       | -          |
| 106-97-8  | 800       | 1900        | -         | -           | -       | -          |
| 141-43-5  | 1         | 2.5         | 3         | 7.6         | -       | 49, 49 Bis |

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

| CAS       | TWA :                 | STEL :                | Ceiling : | Definition : | Criteria : |
|-----------|-----------------------|-----------------------|-----------|--------------|------------|
| 1344-28-1 | 4 mg/m3               |                       |           |              |            |
| 106-97-8  | 600 ppm<br>1450 mg/m3 | 750 ppm<br>1810 mg/m3 |           | Carc         |            |
| 141-43-5  | 1 ppm<br>2,5 mg/m3    | 3 ppm<br>7,6 mg/m3    |           | Sk           |            |

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

2-AMINOETHANOL (CAS: 141-43-5)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

Exposure method:  
Potential health effects:  
DNEL :

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

Exposure method:  
Potential health effects:

**Workers.**

Dermal contact.  
Long term systemic effects.  
1 mg/kg body weight/day

Inhalation.  
Long term local effects.  
3.3 mg of substance/m3

**Consumers.**

Ingestion.  
Long term systemic effects.  
3.75 mg/kg body weight/day

Dermal contact.  
Long term systemic effects.

## METALUSTRE

DNEL : 0.24 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 2 mg of substance/m3

### Predicted no effect concentration (PNEC):

2-AMINOETHANOL (CAS: 141-43-5)

Environmental compartment: Soil.  
PNEC : 0.035 mg/kg

Environmental compartment: Fresh water.  
PNEC : 0.085 mg/l

Environmental compartment: Sea water.  
PNEC : 0.0085 mg/l

Environmental compartment: Intermittent waste water.  
PNEC : 0.025 mg/l

Environmental compartment: Fresh water sediment.  
PNEC : 0.425 mg/kg

Environmental compartment: Marine sediment.  
PNEC : 0.0425 mg/kg

Environmental compartment: Waste water treatment plant.  
PNEC : 100 mg/l

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

## METALUSTRE

Suitable type of protective clothing :

In the event of spraying, wear protective clothing against chemical risks and against sprayed liquid (type 4) in accordance with EN14605 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

### SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

##### General information :

Physical state : Fluid liquid.  
Spray.

##### Important health, safety and environmental information

pH : Not relevant.  
Boiling point/boiling range : 170 °C.  
Vapour pressure (50°C) : Below 110 kPa (1.10 bar).  
Density : < 1  
Water solubility : Insoluble.  
Melting point/melting range : Not specified.  
Self-ignition temperature : 200 °C.  
Decomposition point/decomposition range : 200 °C.  
Chemical combustion heat : Not specified.  
Inflammation time : Not specified.  
Deflagration density : Not specified.  
Inflammation distance : Not specified.  
Flame height : Not specified.  
Flame duration : Not specified.

#### 9.2. Other information

No data available.

### SECTION 10 : STABILITY AND REACTIVITY

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- accumulation of electrostatic charges.
- frost
- flames and hot surfaces

#### 10.5. Incompatible materials

Keep away from :

- strong acids
- strong oxidising agents

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**METALUSTRE**

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

**11.1.1. Substances**

**Acute toxicity :**

2-AMINOETHANOL (CAS: 141-43-5)

Oral route :

LD50 = 1089 mg/kg

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

**11.1.2. Mixture**

No toxicological data available for the mixture.

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

2-AMINOETHANOL (CAS: 141-43-5)

Fish toxicity :

LC50 = 349 mg/l

Species : Cyprinus carpio

Duration of exposure : 96 h

NOEC = 1.2 mg/l

Species : Oryzias latipes

Crustacean toxicity :

EC50 = 65 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

NOEC = 0.85 mg/l

Species : Daphnia magna

Duration of exposure : 21 days

OECD Guideline 211 (Daphnia magna Reproduction Test)

Algae toxicity :

ECr50 = 2.5 mg/l

Species : Scenedesmus capricornutum

Duration of exposure : 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

**12.2.1. Substances**

2-AMINOETHANOL (CAS: 141-43-5)

Biodegradability :

Rapidly degradable.

**12.3. Bioaccumulative potential**

No data available.



**METALUSTRE**

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

AEROSOL: DO NOT PIERCE OR BURN AFTER USE

GIVE TO A RECUPERATOR AGREED. REFER TO PREFECTORAL BY-LAWS IN FORCE.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2016).

**14.1. UN number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable

**14.3. Transport hazard class(es)**

- Classification :



2.1

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

| ADR/RID | Class | Code | Pack gr. | Label | Ident. | LQ  | Provis.         | EQ | Cat. | Tunnel |
|---------|-------|------|----------|-------|--------|-----|-----------------|----|------|--------|
|         | 2     | 5F   | -        | 2.1   | -      | 1 L | 190 327 344 625 | E0 | 2    | D      |

| IMDG | Class | 2°Label  | Pack gr. | LQ    | EMS     | Provis.                   | EQ |
|------|-------|----------|----------|-------|---------|---------------------------|----|
|      | 2.1   | See SP63 | -        | SP277 | F-D,S-U | 63 190 277 327<br>344 959 | E0 |

| IATA | Class | 2°Label | Pack gr. | Passager | Passager | Cargo | Cargo  | note                 | EQ |
|------|-------|---------|----------|----------|----------|-------|--------|----------------------|----|
|      | 2.1   | -       | -        | 203      | 75 kg    | 203   | 150 kg | A145<br>A167<br>A802 | E0 |
|      | 2.1   | -       | -        | Y203     | 30 kg G  | -     | -      | A145<br>A167<br>A802 | E0 |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

## METALUSTRE

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## SECTION 15 : REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

#### - Container information:

No data available.

#### - Particular provisions :

No data available.

#### - Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : anionic surfactants
- less than 5 % : nonionic surfactants
- 15 % or over but less than 30 % : aliphatic hydrocarbons

### 15.2. Chemical safety assessment

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3 :

|        |   |
|--------|---|
| H220   | Extremely flammable gas.                              |
| H280   | Contains gas under pressure; may explode if heated.   |
| H302   | Harmful if swallowed.                                 |
| H304   | May be fatal if swallowed and enters airways.         |
| H312   | Harmful in contact with skin.                         |
| H314   | Causes severe skin burns and eye damage.              |
| H332   | Harmful if inhaled.                                   |
| H335   | May cause respiratory irritation.                     |
| H412   | Harmful to aquatic life with long lasting effects.    |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

### Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.