ONE DAY BOISE B/E

Date: 01/08/2022 Page 1/12

Revision: N°1 (01/08/2022)

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : ONE DAY BOISE BE Product code : 105420-105440

1.2. Relevant identified uses of the substance or mixture and uses advised against

Degreaser, deodorant. Professional use.

1.3. Details of the supplier of the safety data sheet

IPC

10 Quai Malbert, 29200, BREST, FRANCE.

Tel.: +33 (0)2 98 43 45 44. Fax: +33 (0)2 98 44 22 53

ipc@groupe-ipc.com

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

May produce an allergic reaction (EUH208).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS07

Signal Word: WARNING

Additional labeling:

EUH208 Contains 1-(1,2,3,4,5,6,7,8-OCTAHYDRO-2,3,8,8-TETRAMETHYL-2-NAPHTHALENYL)ETHANONE.

May produce an allergic reaction.

EUH208 Contains 4-TERT-BUTYLCYCLOHEXYL ACETATE. May produce an allergic reaction.

EUH208 Contains CEDROL METHYL ETHER. May produce an allergic reaction.

Hazard statements:

H315 Causes skin irritation. H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/face protection.

Precautionary statements - Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

Date: 01/08/2022 Page 2/12 Version: N°1 (01/08/2022) Revision: N°1 (01/08/2022)

ONE DAY BOISE B/E

P305 + P351 + P338IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P332 + P313If skin irritation occurs: Get medical advice/attention. P337 + P313If eye irritation persists: Get medical advice/attention.

Precautionary statements - Disposal:

P501 Dispose of contents/container in accordance with local / regional / national / international regulations.

Other information:

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Composition :			
Identification	(EC) 1272/2008	Note	%
INDEX: 603-096-00-8	GHS07	[1]	2.5 <= x % < 10
CAS: 112-34-5	Wng	[XVII]	
EC: 203-961-6	Eye Irrit. 2, H319		
REACH: 01-2119475104-44			
2-(2-BUTOXYETHOXY)ETHANOL			
INDEX: 603 002 00 5	GHS07, GHS02	[1]	1 <= x % < 2.5
CAS: 64-17-5	Dgr	'	
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43	Eye Irrit. 2, H319		
ETHANOL			
INDEX: 612 131 00 6	GHS07, GHS05, GHS09		1 <= x % < 2.5
CAS: 7173-51-5	Dgr		
EC: 230-525-2	Acute Tox. 4, H302		
	Skin Corr. 1B, H314		
DIDECYLDIMETHYLAMMONIUM	Eye Dam. 1, H318		
CHLORIDE	Aquatic Chronic 2, H411		
	Aquatic Acute 1, H400		
	M Acute = 10		
INDEX: I54464 57 2	GHS07, GHS09		0.1 <= x % < 1
CAS: 54464-57-2	Wng		011 1170 1
EC: 259-174-3	Skin Irrit. 2, H315		
REACH: 01-2119489989-04	Skin Sens. 1B, H317		
1227211 07 2777 107707 01	Aquatic Chronic 1, H410		
1-(1,2,3,4,5,6,7,8-OCTAHYDRO-2,3,8,8-TETR	M Chronic = 1		
AMETHYL-2-NAPHTHALENYL)ETHANONE			
INDEX: 68424 85 1A	GHS07, GHS05, GHS09		0.1 <= x % < 1
CAS: 68424-85-1	Dgr		0.1 1 1 70 1
EC: 270-325-2	Acute Tox. 4, H302		
EC. 270 323 2	Skin Corr. 1B, H314		
QUATERNARY AMMONIUM COMPOUNDS,	Aquatic Acute 1, H400		
BENZYL-C12-16-ALKYLDIMETHYL,	M Acute = 10		
CHLORIDES	Aquatic Chronic 1, H410		
CILORIDES	M Chronic = 1		
INDEX: I32210 23 4	GHS07		0.1 <= x % < 1
CAS: 32210-23-4	Wng		0.1 \- A /0 \ 1
EC: 250-954-9	Skin Sens. 1B, H317		
REACH: 01-2119976286-24	Dam Sens. 1D, 1131/		
KEACH. 01-21199/0200-24			
A TEDT DITTYL CYCLOHEVYL A CETATE			
4-TERT-BUTYLCYCLOHEXYL ACETATE			

ONE DAY BOISE B/E

Date: 01/08/2022 Page 3/12

Revision: N°1 (01/08/2022)

DIDEN 110070 74 7	CHCOZ CHCOO		0.1 < 0/ < 1
INDEX: I19870_74_7	GHS07, GHS09		$0.1 \le x \% < 1$
CAS: 19870-74-7	Wng		
EC: 243-384-7	Skin Sens. 1B, H317		
	Aquatic Acute 1, H400		
CEDROL METHYL ETHER	MAcute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		
INDEX: I469_61_4	GHS08, GHS09, GHS07		$0 \le x \% < 0.1$
CAS: 469-61-4	Dgr		
EC: 207-418-4	Asp. Tox. 1, H304		
	Skin Irrit. 2, H315		
ALPHA-CEDRENE	Aquatic Acute 1, H400		
	MAcute = 10		
	Aquatic Chronic 1, H410		
	M Chronic = 10		

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 603 002 00 5		inhalation: ATE = 51 mg/l 4h
CAS: 64-17-5		
EC: 200-578-6		oral: ATE = 10470 mg/kg BW
REACH: 01-2119457610-43		
ETHANOL		
INDEX: 612_131_00_6		oral: ATE = 658 mg/kg BW
CAS: 7173-51-5		
EC: 230-525-2		
DIDECYLDIMETHYLAMMONIUM		
CHLORIDE		
INDEX: 68424_85_1A		oral: ATE = 795 mg/kg BW
CAS: 68424-85-1		
EC: 270-325-2		
QUATERNARY AMMONIUM COMPOUNDS,		
BENZYL-C12-16-ALKYLDIMETHYL,		
CHLORIDES		1 475 2270 / DW
INDEX: I32210_23_4		oral: ATE = 3370 mg/kg BW
CAS: 32210-23-4		
EC: 250-954-9		
REACH: 01-2119976286-24		
A TENT DUTY CYCL OHEVY A CETATE		
4-TERT-BUTYLCYCLOHEXYL ACETATE		

Information on ingredients:

(Full text of H-phrases: see section 16)

[XVII] Restricted substance under Regulation (EC) No. 1907/2006 (REACH), Annex XVII.

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

In the event of massive inhalation, remove the person to fresh air and keep warm and at rest.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

ONE DAY BOISE B/E

Date: 01/08/2022 Page 4/12 Revision: N°1 (01/08/2022)

In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

ONE DAY BOISE B/E

Date: 01/08/2022 Page 5/12

Revision: N°1 (01/08/2022)

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention:

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep out of reach of children.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

CAS	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes:
112-34-5	67.5	10	101.2	15	-

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

	(,,	•	
CAS	VME:	VME:	Excess	Notes
112-34-5		10 ppm		1.5 (I)
		67 mg/m^3		
64-17-5		200 ppm		4(II)
		380 mg/m^3		

- Belgium (Royal decree of 11/05/2021):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
112-34-5	10 ppm	15 ppm			
	67.5 mg/m ³	101.2 mg/m ³			
64-17-5	1000 ppm				
	1907 mg/m ³				

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
112-34-5	10	67.5	15	101.2	-	-
64-17-5	1000	1900	5000	9500	-	84

- Switzerland (Suva 2021):

5 Table 1 and (5 a. v. a. 2021) .					
CAS	VME	VLE	Valeur 1	olafond	Notations
112-34-5	10 ppm	15 ppm			
	67 mg/m ³	101 mg/m ³			
64-17-5	500 ppm	1000 ppm			
	960 mg/m^3	1920 mg/m ³			

ONE DAY BOISE B/E

Date: 01/08/2022 Page 6/12 Revision: N°1 (01/08/2022)

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
112-34-5	10 ppm	15 ppm			
	67.5 mg/m ³	101.2 mg/m ³			
64-17-5	1000 ppm				
	1920 mg/m ³				

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ETHANOL (CAS: 64-17-5)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 343 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects.

DNEL: 1900 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 950 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Short term systemic effects.

DNEL: 87 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 206 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects.

DNEL: 950 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.
DNEL: 114 mg of substance/m3

Predicted no effect concentration (PNEC):

ETHANOL (CAS: 64-17-5)

Environmental compartment: Soil. PNEC: 0.63 mg/kg

 $\begin{array}{ll} \text{Environmental compartment:} & \text{Fresh water.} \\ \text{PNEC:} & 0.96 \text{ mg/l} \end{array}$

Environmental compartment: Sea water. PNEC: 0.79 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 2.75 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 3.6 mg/kg

Environmental compartment: Marine sediment. PNEC: 2.9 mg/kg

Environmental compartment: Waste water treatment plant.

Date: 01/08/2022 Page 7/12 Revision: N°1 (01/08/2022) Version: N°1 (01/08/2022)

ONE DAY BOISE B/E

PNEC: 580 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Suitable type of protective boots:

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state: Fluid liquid.

Colour

White cream

Odour

Odour threshold: Not stated.

Pleasantly scented

Melting point

Melting point/melting range: Not specified.

Freezing point

Freezing point / Freezing range: Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range: Not specified.

Flammability

Flammability (solid, gas): Not stated. SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (01/08/2022)

ONE DAY BOISE B/E

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%): Not stated. Explosive properties, upper explosivity limit (%): Not stated.

Flash point

Flash point interval: Not relevant.

Auto-ignition temperature

Self-ignition temperature: Not specified.

Decomposition temperature

Decomposition point/decomposition range: Not specified.

pН

pH: 11.20 +/- 0.2. Slightly basic.

pH (aqueous solution): Not stated.

Kinematic viscosity

Viscosity: Not stated.

Solubility

Water solubility: Soluble.
Fat solubility: Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Not relevant.

Density and/or relative density

Density: 1.04 +/- 0.01

Method for determining the density:

ISO 649-2 (Laboratory glassware - Density hydrometers for general purposes

Date: 01/08/2022 Page 8/12 Revision: N°1 (01/08/2022)

- Part 2: Test methods and use).

Relative vapour density

Vapour density: Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid:

- frost
- heat

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

ONE DAY BOISE B/E

Date: 01/08/2022 Page 9/12 Revision: N°1 (01/08/2022)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity:

4-TERT-BUTYLCYCLOHEXYL ACETATE (CAS: 32210-23-4)

Oral route: LD50 = 3370 mg/kg

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)

Oral route: LD50 = 795 mg/kg

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

Oral route: LD50 = 658 mg/kg

Species: Rat

Dermal route : LD50 > 5000 mg/kg

Species: Rat

ETHANOL (CAS: 64-17-5)

Oral route: LD50 = 10470 mg/kg

Species: Rat

OECD Guideline 401 (Acute Oral Toxicity)

 $Dermal \ route: \\ LD50 > 2000 \ mg/kg$

Species: Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a): LC50 = 51 mg/l

Species: Rat

Duration of exposure: 4 h

11.1.2. Mixture

Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards

SECTION 12: ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)

Fish toxicity: LC50 = 0.89 mg/l

Species: Oncorhynchus mykiss Duration of exposure: 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity: EC50 = 0.046 mg/l

Factor M = 10

Species : Daphnia magna Duration of exposure : 48 h

 $0.001 < NOEC \le 0.01 \text{ mg/l}$

ONE DAY BOISE B/E

Factor M = 1

OECD Guideline 211 (Daphnia magna Reproduction Test)

Date: 01/08/2022 Page 10/12 Revision: N°1 (01/08/2022)

Algae toxicity: ECr50 = 0.025 mg/l

Factor M = 10

Species: Selenastrum capricornutum

Duration of exposure: 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

Duration of exposure: 21 days

ETHANOL (CAS: 64-17-5)

LC50 = 13000 mg/lFish toxicity:

Species: Oncorhynchus mykiss

Duration of exposure: 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity: EC50 = 5012 mg/l

Species: Ceriodaphnia dubia Duration of exposure: 48 h

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

LC50 = 0.49 mg/lFish toxicity:

Factor M = 1

Species: Brachydanio rerio Duration of exposure: 96 h

Crustacean toxicity: EC50 = 0.03 mg/l

> Species: Daphnia magna Duration of exposure: 48 h

ECr50 = 0.12 mg/lAlgae toxicity:

Species: Scenedesmus capricornutum

Duration of exposure: 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of Member States and will be provided with their request or at the request of a detergent manufacturer.

12.2.1. Substances

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)

Rapidly degradable. Biodegradability:

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

Biodegradability: Rapidly degradable.

ETHANOL (CAS: 64-17-5)

Biodegradability: Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

Bioaccumulation: BCF = 81

12.4. Mobility in soil

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (01/08/2022)

ONE DAY BOISE B/E

Date: 01/08/2022 Page 11/12 Revision: N°1 (01/08/2022)

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14: TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

14.6. Special precautions for user

-

14.7. Maritime transport in bulk according to IMO instruments

-

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No 1272/2008 amended and its amendments EU . (ATP)

- Container information:

No data available.

-Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture contains at least one restricted substance under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach. Please refer to Section 3 to identify the substance involved.

- Particular provisions:

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006):

- less than 5% of: cationic surfactants
- less than 5% of: non-ionic surfactants
- perfumes

ONE DAY BOISE B/E

Date: 01/08/2022 Page 12/12 Revision: N°1 (01/08/2022)

- allergenic fragrances:

coumarin

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H225	Highly flammable liquid and vapour.
11223	ringiny naminable fiquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations:

LD50: The dose of a test substance resulting in 50% lethality in a given time period.

LC50: The concentration of a test substance resulting in 50% lethality in a given period.

EC50: The effective concentration of substance that causes 50% of the maximum response.

ECr50: The effective concentration of substance that causes 50% reduction in growth rate.

NOEC: The concentration with no observed effect.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE: Acute Toxicity Estimate

BW: Body Weight

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

UFI: Unique formulation identifier. STEL: Short-term exposure limit

TWA: Time Weighted Averages

TMP: French Occupational Illness table

TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.