## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name: PROSOLV LINGETTES

Product code: 102251.

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Registered company name: IPC S.A.S..

Address: 10, Quai Commandant Malbert - CS 71821.29218.BREST Cedex 1.France.

Telephone: +33 (0)2 98 43 45 44. Fax: +33 (0)2 98 44 22 53.

ipc@groupe-ipc.com http://www.ipc-sa.com

## 1.4. Emergency telephone number: +33 (0)2.98.43.45.44.

Association/Organisation: .

## **SECTION 2 : HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

## In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

May produce an allergic reaction (EUH208).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

### 2.2. Label elements

Biocidal detergent mixture (see section 15).

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS02 GHS07

Signal Word:

DANGER

Additional labeling:

EUH208 Contains (R)-P-MENTHA-1,8-DIENE. May produce an allergic reaction.

Hazard statements :

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Precautionary statements - Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary statements - Disposal:

P501 Dispose of contents/container to ...

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances > 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

### **Composition:**

Composition .			
Identification	(EC) 1272/2008	Note	%
INDEX: 603_002_00_5	GHS07, GHS02	[1]	50 <= x % < 100
CAS: 64-17-5	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
	Eye Irrit. 2, H319		
BIOETHANOL			
INDEX: 603_117_00_0	GHS07, GHS02	[1]	$2.5 \le x \% \le 10$
CAS: 67-63-0	Dgr		
EC: 200-661-7	Flam. Liq. 2, H225		
REACH: 01-2119457558-25-XXXX	Eye Irrit. 2, H319		
	STOT SE 3, H336		
PROPAN-2-OL			
INDEX: 601_029_007A	GHS07, GHS09, GHS08, GHS02	[1]	$0 \le x \% \le 2.5$
CAS: 5989-27-5	Dgr		
EC: 227-813-5	Flam. Liq. 3, H226		
REACH: 01-2119493353-35	Asp. Tox. 1, H304		
	Skin Irrit. 2, H315		
(R)-P-MENTHA-1,8-DIENE	Skin Sens. 1, H317		
	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		

# **Specific concentration limits:**

Identification	Specific concentration limits	ATE
INDEX: 603_117_00_0		dermal: ATE = 13900 mg/kg BW
CAS: 67-63-0		oral: ATE = 5840 mg/kg BW
EC: 200-661-7		
REACH: 01-2119457558-25-XXXX		
PROPAN-2-OL		

### **Information on ingredients:**

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

## **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

# 4.1. description of first aid measures

## In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

## In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

# In the event of splashes or contact with skin:

In the event of an allergic reaction, seek medical attention.

### In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## **SECTION 5: FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

## 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

## Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

## 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

## For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

## 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

## SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

#### Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

# Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

# Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.

# Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

# **Packaging**

Always keep in packaging made of an identical material to the original.

# 7.3. Specific end use(s)

No data available.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

### Occupational exposure limits:

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
64-17-5		1000 ppm		A3	
67-63-0	200 ppm	400 ppm		A4; BEI	

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME:	VME:	Excess	Notes
64-17-5		200 ppm		4(II)
		380 mg/m <sup>3</sup>		
67-63-0		200 ppm		2(II)
		$500 \text{ mg/m}^3$		
5989-27-5		5 ppm		4(II)
		$28 \text{ mg/m}^3$		

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
64-17-5	1000	1900	5000	9500	-	84
67-63-0	-	-	400	980	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
64-17-5	1000 ppm				
	1920 mg/m <sup>3</sup>				
67-63-0	400 ppm	500 ppm			
	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>			

## Derived no effect level (DNEL) or derived minimum effect level (DMEL):

PROPAN-2-OL (CAS: 67-63-0)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 888 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 500 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 26 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 319 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects. DNEL: 89 mg of substance/m3

# **Predicted no effect concentration (PNEC):**

PROPAN-2-OL (CAS: 67-63-0)

Environmental compartment: Soil.

PNEC: 28 mg/kg

Environmental compartment: Fresh water. PNEC: 140.9 mg/l

Environmental compartment: Sea water. PNEC: 140.9 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 140.9 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 552 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 2251 mg/l

# 8.2. Exposure controls

## Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

# - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

# - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

Physical state

Physical state: Fluid liquid.

N/A

Colour

Unspecified

Odour

Odour threshold: Not stated.

Melting point

Melting point/melting range: Not specified.

Freezing point

Freezing point / Freezing range: Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range: > 35°C

Flammability

Flammability (solid, gas): Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%):

Not stated.

Explosive properties, upper explosivity limit (%):

Not stated.

Flash point

Flash Point: 21.00 °C.

**Auto-ignition temperature** 

Self-ignition temperature : Not specified.

**Decomposition temperature** 

Decomposition point/decomposition range: Not specified.

pН

pH: Not relevant.
pH (aqueous solution): Not stated.

Kinematic viscosity

Viscosity: Not stated.

Solubility

Water solubility: Dilutable.
Fat solubility: Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Not relevant.

Density and/or relative density

Density: 0.865

Relative vapour density

Vapour density: Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

# **SECTION 10: STABILITY AND REACTIVITY**

### 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

## 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- accumulation of electrostatic charges.

- heating
- heat
- flames and hot surfaces

# 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

## SECTION 11: TOXICOLOGICAL INFORMATION

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

### 11.1.1. Substances

Acute toxicity:

PROPAN-2-OL (CAS: 67-63-0)

Oral route : LD50 = 5840 mg/kg

Species: Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 = 13900 mg/kg

Species: Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist): LC50 > 25 mg/l

Species: Rat

OECD Guideline 403 (Acute Inhalation Toxicity)

**Respiratory or skin sensitisation:** 

PROPAN-2-OL (CAS: 67-63-0)

Local lymph node stimulation test:

Non-Sensitiser.

Species: Guinea pig

OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

PROPAN-2-OL (CAS: 67-63-0)

Mutagenesis (in vivo): Negative.

Species : Mouse

OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Mutagenesis (in vitro): Negative.

Species: Bacteria

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Carcinogenicity:

PROPAN-2-OL (CAS: 67-63-0)

Carcinogenicity Test: Negative.

No carcinogenic effect. Species: Mouse

OECD Guideline 451 (Carcinogenicity Studies)

## Reproductive toxicant:

PROPAN-2-OL (CAS: 67-63-0) No toxic effect for reproduction

#### 11.1.2. Mixture

# Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

### 11.2. Information on other hazards

# **SECTION 12: ECOLOGICAL INFORMATION**

### 12.1. Toxicity

# 12.1.1. Substances

(R)-P-MENTHA-1,8-DIENE (CAS: 5989-27-5)

Fish toxicity: LC50 < 1 mg/l

Duration of exposure: 96 h

Crustacean toxicity: EC50 < 1 mg/l

Duration of exposure: 48 h

Algae toxicity: ECr50 < 1 mg/l

Duration of exposure: 72 h

PROPAN-2-OL (CAS: 67-63-0)

Fish toxicity: LC50 = 9640 mg/l

Species : Pimephales promelas Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity: EC50 = 9714 mg/l

Species : Daphnia magna Duration of exposure : 24 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity: ECr50 > 100 mg/l

Species : Raphidocelis subcapitata Duration of exposure : 72 h

## **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

## 12.2. Persistence and degradability

### 12.2.1. Substances

(R)-P-MENTHA-1,8-DIENE (CAS: 5989-27-5)

Biodegradability: no degradability data is available, the substance is considered as not degrading

quickly.

PROPAN-2-OL (CAS: 67-63-0)

Chemical oxygen demand : DCO = 2.294 g/g

Five-day biochemical oxygen demand : DBO5 = 1.171 g/g

Biodegradability: Rapidly degradable.

DBO5/DCO = 0.51

## 12.3. Bioaccumulative potential

### 12.3.1. Substances

PROPAN-2-OL (CAS: 67-63-0)

Octanol/water partition coefficient:

 $\log \text{Koe} = 0.05$ 

OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

# 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

No data available.

# 12.6. Endocrine disrupting properties

No data available.

# 12.7. Other adverse effects

No data available.

# SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

# 14.1. UN number or ID number

3175

# 14.2. UN proper shipping name

UN3175=SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C

(bioethanol, propan-2-ol)

# 14.3. Transport hazard class(es)

- Classification:



4.1

## 14.4. Packing group

II

# 14.5. Environmental hazards

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	4.1	F1	П	4.1	40	1 kg	216 274 601	E2	2.	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	4.1	-	II	1 kg	F-A. S-I	216 274	E2	Category B	-

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	4.1	-	II	445	15 kg	448	50 kg	A46	E2
	4.1	_	II	Y441	5 kg	-	-	A46	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

#### - Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

### - Particular provisions :

No data available.

# - Labelling for detergents (EC Regulation No. 648/2004,907/2006):

- allergenic fragrances:

(r)-p-mentha-1,8-diene

citral

citronellol

# - Labelling for biocidal products (Regulation (UE) n° 528/2012) :

Name	CAS	%	Product-type
BIOETHANOL	64-17-5	643.47 g/kg	01
			02
			04
PROPAN-2-OL	67-63-0	99.80 g/kg	01
			02
			04

Product-type 1: Human hygiene.

Product-type 2: Disinfectants and algaecides not intended for direct application to humans or animals.

Product-type 4: Food and feed area.

## 15.2. Chemical safety assessment

No data available.

## **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

## Wording of the phrases mentioned in section 3:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### **Abbreviations:**

LD50: The dose of a test substance resulting in 50% lethality in a given time period.

LC50: The concentration of a test substance resulting in 50% lethality in a given period.

EC50: The effective concentration of substance that causes 50% of the maximum response.

ECr50: The effective concentration of substance that causes 50% reduction in growth rate.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE: Acute Toxicity Estimate

BW: Body Weight

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

STEL : Short-term exposure limit TWA : Time Weighted Averages

TMP : French Occupational Illness table TLV : Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.