# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 12/05/2021 Revision date: 21/05/2024 Supersedes version of: 01/02/2023 Version: 3.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : STORM MONOÏ

UFI : 107503 Product code : Aerosol

Product identification

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

### Manufacturer

**IPC** 

10 Quai Malbert, 29200, BREST, FRANCE.

Tel.: +33 (0)2 98 43 45 44. Fax: +33 (0)2 98 44 22 53 ipc@groupe-ipc.com

### 1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
Eye Irrit. 2 H319
Full text of hazard classes, H- and EUH-statements: see section 16

## Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Causes serious eye irritation.

# 2.2. Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02

GHS07

Signal word (CLP) : Danger

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe spray.

P271 - Use only outdoors or in a well-ventilated area.

P403 - Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

EUH-statements : EUH208 - Contains Coumarin(91-64-5). May produce an allergic reaction.

Extra phrases : Not to be used for any purpose other than the one the product was designed for.

Seek medical attention if ill effect develops.

For professional use only.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol substance with national workplace exposure limit(s) (FR)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-	40 – 60	Flam. Liq. 2, H225 Eye Irrit. 2, H319
N-Butane (contenant <0.1% butadiène) (Propellant gas (Aerosol))	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	20 – 30	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
propane (Propellant gas (Aerosol))	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	10 – 20	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
Isobutane (containing < 0,1 % butadiene) (Propellant gas (Aerosol)) (Note C)(Note U)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	8 – 10	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
Diethyl phthalate substance with national workplace exposure limit(s) (FR)	CAS-No.: 84-66-2 EC-No.: 201-550-6 REACH-no: 01-2119486682- 27	2-5	Not classified

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl alcohol	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5	0.5 – 1	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight)
Alcohols C12-14, ethoxylated (>2-5EO)	CAS-No.: 68439-50-9	0.5 – 1	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Coumarin	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	0.1 – 0.5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Sens. 1B, H317
2-methylpropan-2-ol substance with national workplace exposure limit(s) (FR)	CAS-No.: 75-65-0 EC-No.: 200-889-7 EC Index-No.: 603-005-00-1 REACH-no: 01-2119444321- 51	< 0.1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Eye Irrit. 2, H319 STOT SE 3, H335

Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
ethanol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610- 43	(50 ≤ C < 100) Eye Irrit. 2, H319	

Comments : Calculation of aerosol labeling excluding gas

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the

supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied

gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:. Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section

2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

Remove person to fresh air and keep comfortable for breathing. First-aid measures after inhalation

First-aid measures after skin contact Wash skin with plenty of water. Seek medical attention if ill effect or irritation develops. First-aid measures after eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting.

Allow the victim to rest.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this

material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions.

21/05/2024 (Revision date) GB - en 3/14

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions. Ingestion unlikely.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Reactivity in case of fire : Prevent fire fighting water from entering the environment.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

# 5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. During a fire, projections ignited aerosol that burst under excessive pressure have to be controlled. To avoid overpressure, cool aerosols with water. Prevent fire fighting

water from entering the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage. Measures to take in the case of crushing or piercing aerosols, causing the leaking of products contained in aerosols. Ventilate area. Do not smoke. Remove ignition sources. Provide local exhaust or general room ventilation.

Evacuate and limit access. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes. Do not touch spilled material. Evacuate area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so. Provide adequate ventilation.

Do not inhale vapour.

# 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Mechanically recover the product. Clean spills promptly. Collect the residue by means of a

. Mechanically recover the product. Clean spins promptly. Collect the residue by means of a

non-combustible absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

21/05/2024 (Revision date) GB - en 4/14

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.4. Reference to other sections

For further information refer to section 13.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed Precautions for safe handling

- : Not expected to present a significant hazard under anticipated conditions of normal use.
  - Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Not to be used for any purpose other than the one the product was designed for. Do not breathe gas, fumes, vapour or spray. During the handling of a pallet, you have to take all precaution to avoid a start of a n accident perforation of the aerosol by a fork-lift truck.

During the load and unloading of the vehicle, you have to take all the precaution to avoid a fall a aerosol.

Do not spray tha aerosol neither close nor towards a flame, a white-hot body, an electrical appliance in runing, DO NOT SMOCKING. Container under pressure. Do not drill or burn even after use. Store and handle as though always a serious potential fire/explosion and health hazard exists.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Storage conditions

- : Keep in a cool, well-ventilated place away from heat. Proper grounding procedures to avoid static electricity should be followed. Use grounded electrical/mechanical equipment.
- : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

  Recommendations applicable to warehouses and reserves which are stored aerosols.

  It is recommended to de-normalize aerosols in stock. The " aerosol " or area must be set with a wire mesh of mesh max 5cm, forming a cage or using walls to avoid splashing the aerosols may ignite rest of the stock. Do not smoke.

To reduce the risk of falling, should position the pallet closest to the ground. If the packages are stacked, it should ensure that those lower layers do not crash (risk of leakage through compression).

It is recommended:

- Ventilate the premises and not store any sprays near heat sources, including sunlight, sparks and open flames
- To use the procedure of fire when working . Store in a dry, well ventilated place .
- Store always product in container of same material as original container.

# Packaging materials

No additional information available

7.3. Specific end use(s)

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

# 8.1.1 National occupational exposure and biological limit values

N-Butane (contenant <0.1% butadiène) (106-97-8)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	1450 mg/m³	
	600 ppm	
WEL STEL (OEL STEL)	1810 mg/m³	

21/05/2024 (Revision date) GB - en 5/14

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## N-Butane (contenant <0.1% butadiène) (106-97-8)

750 ppm

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

# 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

### Personal protective equipment:

Wear recommended personal protective equipment.

#### Personal protective equipment symbol(s):





# 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses	Droplet		EN 166

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Skin protection appropriate to the conditions of use should be provided

#### Hand protection:

Protective gloves. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

## 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : colourless to slightly yellow.

Odour : Floral.

Odour threshold : Not available

Melting point : Not applicable

Freezing point : Not available

Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit : Not available : Not available Upper explosion limit : < 0 °C Flash point Auto-ignition temperature : Not available : Not available Decomposition temperature рΗ : Not available Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density : 0.82 (PA) Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

#### 9.2. Other information

# 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 94 %

9.2.2. Other safety characteristics

VOC content : 95.2 % (634.1 g/l)

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Extremely high or low temperatures. Do not expose to temperatures exceeding 50 °C/ 122 °F.

# 10.5. Incompatible materials

Strong acids. Strong bases.

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# **SECTION 11: Toxicological information**

11.1. Information on hazard classes as defin	ed in Regulation (EC) No 1272/2008		
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	<ul> <li>Not classified (Based on available data, the classification criteria are not met)</li> <li>Not classified (Based on available data, the classification criteria are not met)</li> <li>Not classified (Based on available data, the classification criteria are not met)</li> </ul>		
ethanol (64-17-5)			
LD50 oral	10470 mg/kg		
LD50 dermal	15800 mg/kg		
LC50 Inhalation - Rat	50000 mg/m³		
2-methylpropan-2-ol (75-65-0)			
LD50 dermal	> 2000 mg/kg		
benzyl alcohol (100-51-6)			
LD50 oral rat	1230 mg/kg		
LD50 oral	1620 mg/kg		
LC50 Inhalation - Rat (Dust/Mist)	> 4.178 mg/l/4h		
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)		
Serious eye damage/irritation	: Causes serious eye irritation.		
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)		
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)		
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)		
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)		
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)		
2-methylpropan-2-ol (75-65-0)			
STOT-single exposure	May cause respiratory irritation.		
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)		
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)		
STORM MONOÏ			

# 11.2. Information on other hazards

No additional information available

Product identification

# **SECTION 12: Ecological information**

-		-	. 1	_			•			
м	₽.				_	v		~	12	v

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse	
	effects in the environment.	

Hazardous to the aquatic environment, short-term : Not classified (Based on available data, the classification criteria are not met) (acute)

Aerosol

Hazardous to the aquatic environment, long-term : Not classified (Based on available data, the classification criteria are not met) (chronic)

(GITOTIO)	on one	
ethanol (64-17-5)		
LC50 - Fish [1]	11200 mg/l	
LC50 - Fish [2]	13000 mg/l	
EC50 - Crustacea [1]	12340 mg/l	

21/05/2024 (Revision date) GB - en 8/14

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanol (64-17-5)		
EC50 72h - Algae [1]	275 mg/l	
2-methylpropan-2-ol (75-65-0)		
EC50 - Crustacea [1]	933 mg/l	
benzyl alcohol (100-51-6)		
EC50 - Crustacea [1]	360 mg/l	
EC50 - Crustacea [2]	230 mg/l	
EC50 72h - Algae [1]	770 mg/l Pseudokirchneriella subcapitata	
EC50 96h - Algae [1]	640 mg/l scenedesmus quadricauda	
NOEC chronic algae	310 mg/l Pseudokirchneriella subcapitata	
12.2. Persistence and degradability		
STORM MONOÏ		

STORM MONOÏ			
Persistence and degradability	Rapidly degradable		
ethanol (64-17-5)			
Persistence and degradability	Rapidly degradable		
2-methylpropan-2-ol (75-65-0)			
Persistence and degradability	Readily biodegradable.		
Biodegradation	99 %		
Alcohols C12-14, ethoxylated (>2-5EO) (68439	-50-9)		
Persistence and degradability	Rapidly degradable		
benzyl alcohol (100-51-6)			
Persistence and degradability	Rapidly degradable		
Coumarin (91-64-5)			
Persistence and degradability	Rapidly degradable		
Diethyl phthalate (84-66-2)			
Persistence and degradability	Rapidly degradable		
N-Butane (contenant <0.1% butadiène) (106-9	7-8)		
Persistence and degradability	Half-life time in water: <2.6 d Half-life time in air: 3.2 d.		
propane (74-98-6)			
Persistence and degradability	Rapidly degradable		
Biodegradation	< 60 % 28d		
Isobutane (containing < 0,1 % butadiene) (75-	Isobutane (containing < 0,1 % butadiene) (75-28-5)		
Persistence and degradability	Rapidly degradable		

# 12.3. Bioaccumulative potential

N-Butane (contenant <0.1% butadiène) (106-9	7-8)
Bioaccumulative potential	Not potentially bioaccumulable.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)	
Bioaccumulative potential	No information available.

# 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

# 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Regional waste regulation

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information Ecological information HP Code

- : Disposal must be done according to official regulations.
- Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Disposal must be done according to official regulations.
- Disposal must be done according to official regulations. Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
- : Do not re-use empty containers.
- : Avoid release to the environment.
- : HP3 "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20  $^{\circ}\text{C}$  and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	umber				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950	
14.2. UN proper shippin	14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS	
Transport document description					
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID	
14.3. Transport hazard	14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1	
	2	2	2	2	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental haz	zards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No	
No supplementary information	on available	1	1	1	

### 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207

Special pooling provisions (ADR) : P207

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

# Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0 Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

### Air transport

No data available

### **Inland waterway transport**

No data available

### Rail transport

No data available

# 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Other information, restriction and prohibition : Aerosol Generator Directive 75/324/EEC and its adaptations. regulations

# REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	
3(a)	STORM MONOÏ; ethanol; 2-methylpropan-2-ol	
3(b)	STORM MONOÏ; ethanol; 2-methylpropan-2-ol; Alcohols C12-14, ethoxylated (>2-5EO); benzyl alcohol; Coumarin	
3(c)	Alcohols C12-14, ethoxylated (>2-5EO)	
40.	ethanol ; 2-methylpropan-2-ol ; N-Butane (contenant <0.1% butadiène) ; propane ; Isobutane (containing < 0,1 % butadiene)	

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### **Dual-Use Regulation (428/2009)**

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

# VOC Directive (2004/42)

VOC content : 95.2 % (634.1 g/l)

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

# **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
9.1	Relative density	Added	

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acr	onyms:
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aerosol 1	Aerosol, Category 1	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
EUH208	Contains Coumarin(91-64-5). May produce an allergic reaction.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H302	Harmful if swallowed.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H400	Very toxic to aquatic life.	
H412	Harmful to aquatic life with long lasting effects.	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	

The classification complies with

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

: ATP 12