SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : STORM ROMANCE Product code : 107120

1.2. Relevant identified uses of the substance or mixture and uses advised against

Deodorant

1.3. Details of the supplier of the safety data sheet

IPC

10 Quai Malbert, 29200, BREST, FRANCE. Tel. : +33 (0)2 98 43 45 44. Fax : +33 (0)2 98 44 22 53 ipc@groupe-ipc.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02	
Signal Word :	
DANGER	
Hazard statements :	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
Precautionary statements - Prevention	:
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
Precautionary statements - Storage :	
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.
Other information :	
	Do not use the product in another way of what it is intended to. Use and store only in a well-ventilated area. Do not spray for a long time.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 601-004-00-0	GHS02, GHS04	С	25 <= x % < 50
CAS: 106-97-8	Dgr	[1]	
EC: 203-448-7	Flam. Gas 1, H220	[7]	
BUTANE			
INDEX: 603 002 005A	GHS07, GHS02	[1]	10 <= x % < 25
CAS: 64-17-5	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43	Eye Irrit. 2, H319		
ETHANOL			
INDEX: 601-004-00-0	GHS02, GHS04	С	10 <= x % < 25
CAS: 75-28-5	Dgr	[1]	
EC: 200-857-2	Flam. Gas 1, H220	[7]	
AND ISOBUTANE			
INDEX: 601-003-00-5	GHS02, GHS04	[1]	2.5 <= x % < 10
CAS: 74-98-6	Dgr	[7]	
EC: 200-827-9	Flam. Gas 1, H220		
PROPANE			
INDEX: I25265 71 8		[1]	0 <= x % < 2.5
CAS: 25265-71-8		[-]	
EC: 246-770-3			
REACH: 01-2119456811-38			
DIPROPYLENE GLYCOL			
INDEX: A04322/07	GHS07, GHS09		0 <= x % < 2.5
CAS: 68439-50-9	Wng		
EC: 500-213-3	Eye Irrit. 2, H319		
	Aquatic Chronic 3, H412		
ALCOHOLS C12-14, ETHOXYLATED	Aquatic Acute 1, H400		
	M Acute = 1		
Specific concentration limits:	· ·	L	•

specific concentration millis.			
Identification	Specific concentration limits	ATE	
INDEX: 603_002_005A	Eye Irrit. 2: H319 C>= 50%		
CAS: 64-17-5			
EC: 200-578-6			
REACH: 01-2119457610-43			
ETHANOL			

Information on ingredients :

(Full text of H-phrases: see section 16)

Substances may not have a REACH Registration No.. because they are manufactured / imported in quantities less than 1 ton / year, or they are complex substances or they are exempted from registration under REACH.

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In case of massive inhalation transport the patient outdoors and keep him for the warmth and for the rest.

Consult doctor if symptoms develop.
In the event of splashes or contact with eyes :
Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.
Consult a doctor with the label.
In the event of splashes or contact with skin :
Lave bem a pele com água. Se a irritação persistir, chame um médico.
In the event of swallowing :
In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
Keep the person exposed at rest. Do not force vomiting.
Seek medical attention, showing the label.
If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.
4.2. Most important symptoms and effects, both acute and delayed
No data available.
4.3. Indication of any immediate medical attention and special treatment needed
Specific and immediate treatment :
No data available.
Information for the doctor :
No data available.
SECTION 5 : FIREFIGHTING MEASURES
Flammable.
Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.
5.1. Extinguishing media
Keep packages near the fire cool, to prevent pressurised containers from bursting.
Suitable methods of extinction
In the event of a fire, use :
- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam - multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)
Prevent the effluent of fire-fighting measures from entering drains or waterways.
Unsuitable methods of extinction
In the event of a fire, do not use : - water jet
5.2. Special hazards arising from the substance or mixture A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
Do not breathe in smoke.
In the event of a fire, the following may be formed :
- carbon monoxide (CO)
- carbon dioxide (CO2)
5.3. Advice for firefighters
Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous
insulating breathing apparatus.
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.
SECTION 6 : ACCIDENTAL RELEASE MEASURES
6.1. Personal precautions, protective equipment and emergency procedures
Consult the safety measures listed under headings 7 and 8.
For non first aid worker
Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

See Section 7 for information on safe handling.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

- ACGIH TLV (A	American Conferei					values, 2010
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
106-97-8	1000 ppm					
64-17-5		1000 ppm		A3		
75-28-5	1000 ppm					
74-98-6	1000 ppm					
Germany - AG	W (BAuA - TRGS	900, 08/08/2019	9):			
CAS	VME :	VME :	Excess	Notes	7	
106-97-8		1000 ppm		4(II)	-	
		2400 mg/m ³				
64-17-5		200 ppm		4(II)		
		380 mg/m ³				
75-28-5		1000 ppm		4(II)		
		2400 mg/m ³				
74-98-6		1000 ppm		4(II)		
		1800 mg/m ³				
25265-71-8		100 E mg/m ³		2(II)		
	(4 dy 10/11/2020)		1	-()		
CAS	<u>é du 19/11/2020) :</u> TWA :	STEL :	Cailing	Definition :	Critoria	
CAS 106-97-8	I WA:		Ceiling :	Definition :	Criteria :	_
100-97-8		980 ppm 2370 mg/m ³				
64-17-5	1000 ppm	2570 ing/m ³				_
04-17-3						
75 00 5	1907 mg/m ³	000				_
75-28-5		980 ppm				
74.09.6	1000	2370 mg/m ³				_
74-98-6	1000 ppm					
	ED984 / 2020-15					
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3:	Notes :	TMP No
106-97-8	800	1900	-	-	-	-
64-17-5	1000	1900	5000	9500	-	84
- Spain (Instituto	Nacional de Segu	ridad e Higiene	en el Trabajo (I	NSHT), 2019)	:	
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
106-97-8	1000 ppm					
64-17-5		1 ppm		8		
		1.91 mg/m ³				
74-98-6	1000 ppm					
- Switzerland (S	UVAPRO 2019) :	•				
CAS	VME	VLE	Valeur plafond	Notations	7	
106-97-8	800 ppm	3200 mg/m ³	valour platona	riotutions	-	
100 97 0	1900 mg/m ³	7600 fc/m ³				
64-17-5	500 ppm	1000 mg/m ³			-	
011/0	960 mg/m ³	1920 fc/m ³				
75-28-5					-	
.5 20 5		3200 mg/m ³				
	800 ppm	3200 mg/m ³ 7600 fc/m ³				
74-98-6	800 ppm 1900 mg/m ³	7600 fc/m ³			_	
74-98-6	800 ppm 1900 mg/m ³ 1000 ppm	7600 fc/m ³ 4000 mg/m ³			_	
	800 ppm 1900 mg/m ³ 1000 ppm 1800 mg/m ³	7600 fc/m ³ 4000 mg/m ³ 7200 fc/m ³			-	
25265-71-8	800 ppm 1900 mg/m ³ 1000 ppm 1800 mg/m ³ 140 ppm	7600 fc/m ³ 4000 mg/m ³ 7200 fc/m ³ 280 mg/m ³		2020	-	
25265-71-8 - UK / WEL (We	800 ppm 1900 mg/m ³ 1000 ppm 1800 mg/m ³ 140 ppm orkplace exposure	7600 fc/m ³ 4000 mg/m ³ 7200 fc/m ³ 280 mg/m ³ limits, EH40/200				
25265-71-8 - UK / WEL (We CAS	800 ppm 1900 mg/m ³ 1000 ppm 1800 mg/m ³ 140 ppm orkplace exposure TWA :	7600 fc/m ³ 4000 mg/m ³ 7200 fc/m ³ 280 mg/m ³ limits, EH40/200 STEL :	05, Fourth Editi Ceiling :	Definition :	Criteria :	_
25265-71-8 - UK / WEL (We CAS	800 ppm 1900 mg/m ³ 1000 ppm 1800 mg/m ³ 140 ppm orkplace exposure TWA : 600 ppm	7600 fc/m ³ 4000 mg/m ³ 7200 fc/m ³ 280 mg/m ³ limits, EH40/200 STEL : 750 ppm			Criteria :	
25265-71-8 - UK / WEL (Wo CAS 106-97-8	800 ppm 1900 mg/m ³ 1000 ppm 1800 mg/m ³ 140 ppm orkplace exposure TWA : 600 ppm 1450 mg/m ³	7600 fc/m ³ 4000 mg/m ³ 7200 fc/m ³ 280 mg/m ³ limits, EH40/200 STEL :		Definition :	Criteria :	
25265-71-8 - UK / WEL (We	800 ppm 1900 mg/m ³ 1000 ppm 1800 mg/m ³ 140 ppm orkplace exposure TWA : 600 ppm	7600 fc/m ³ 4000 mg/m ³ 7200 fc/m ³ 280 mg/m ³ limits, EH40/200 STEL : 750 ppm		Definition :	Criteria :	

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

DIPROPYLENE GLYCOL (CAS: 25265-71-8)

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

ETHANOL (CAS: 64-17-5) **Final use:** Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Predicted no effect concentration (PNEC):

DIPROPYLENE GLYCOL (CAS: 25265-71-8) Environmental compartment: PNEC :

Environmental compartment: PNEC :

Environmental compartment: PNEC : Workers. Dermal contact. Long term systemic effects. 84 mg/kg body weight/day

Inhalation. Long term systemic effects. 238 mg of substance/m3

Consumers. Ingestion. Long term systemic effects. 24 mg/kg body weight/day

Dermal contact. Long term systemic effects. 51 mg/kg body weight/day

Inhalation. Long term systemic effects. 70 mg of substance/m3

Workers. Dermal contact. Long term systemic effects.

343 mg/kg body weight/day Inhalation. Long term systemic effects.

950 mg of substance/m3

Consumers. Ingestion. Long term systemic effects. 87 mg/kg body weight/day

Dermal contact. Long term systemic effects. 206 mg/kg body weight/day

Inhalation. Long term systemic effects. 114 mg of substance/m3

Soil. 0.025 mg/kg

Fresh water. 0.1 mg/l

Sea water. 0.01 mg/l

- Made under licence of European Label System® MSDS software from InfoDyne - http://www.infodyne.fr -

Environmental compartment:	Intermittent waste water.
PNEC :	1 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.238 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.024 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	1000 mg/l
Environmental compartment:	Vermivore predators (oral).
PNEC :	313 mg/kg
ETHANOL (CAS: 64-17-5) Environmental compartment: PNEC :	Soil. 0.63 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.96 mg/l
Environmental compartment:	Sea water.
PNEC :	0.79 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	2.75 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	3.6 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	2.9 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	580 mg/l
Environmental compartment:	Vermivore predators (oral).
PNEC :	0.38 mg/kg

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

- Type of gloves recommended :
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

Let the glove manufacturer advise you on the choice of gloves and their duration of use for your operating conditions

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- AX

Particle filter according to standard EN143 :

- P1

Types, classes and filters for respiratory protection above are recommended in case of confrontation at concentrations higher than the exposure limits specified under 8.1. (Control parameters) .They should be adjusted according to actual conditions. they may not be necessary if the product is used outdoors or in a well ventilated area.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES	
9.1. Information on basic physical and chemical properties	
Physical state	
Physical state :	Fluid liquid.
Colour	
Unspecified	
Odour	
Odour threshold :	Not stated.
Melting point	
Melting point/melting range :	Not specified.
Freezing point	
Freezing point / Freezing range :	Not stated.
Boiling point or initial boiling point and boiling range	
Boiling point/boiling range :	Not specified.
Flammability	
Flammability (solid, gas) :	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%):	Not stated.
Explosive properties, upper explosivity limit (%):	Not stated.
Flash point	
Flash point interval :	Not relevant.
Auto-ignition temperature	
Self-ignition temperature :	Not specified.
Decomposition temperature	
Decomposition point/decomposition range :	Not specified.
рН	
pH :	Not relevant.
pH (aqueous solution) :	Not stated.
Kinematic viscosity	
Viscosity :	Not stated.
Viscosity:	$v < 7 \text{ mm2/s} (40^{\circ}\text{C})$
Solubility	
Water solubility :	Insoluble.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C) :	Not relevant.
Density and/or relative density	
Density :	< 1
Relative vapour density	
Vapour density :	Not stated.

Particle characteristics

N/A

A

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

<u> </u>	
No data available.	
Aerosols	
Chemical combustion heat :	Not specified.
Inflammation time :	Not specified.
Deflagration density :	Not specified.
Inflammation distance :	Not specified.
Flame height :	Not specified.
Flame duration :	Not specified.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Aouto	toxicity	•
Acute	toxicity	•

ETHANOL (CAS: 64-17-5)	LD50 > 5000 mg/kg
Oral route :	Species : Rat
Inhalation route (Vapours) :	LC50 > 1000 mg/l Species : Mouse

11.1.2. Mixture

Skin corrosion/skin irritation :

Based on available data; the classification criteria are not met.

Serious damage to eyes/eye irritation :

Based on available data the classification criteria are not met.

Respiratory or skin sensitisation : To be translated (XML)	
Germ cell mutagenicity :	
Based on available data; the classification criter	ia are not met
Carcinogenicity :	
Based on available data; the classification criter.	ia are not met.
Reproductive toxicant :	
Based on available data; the classification criter	ia are not met.
Specific target organ systemic toxicity - single e	exposure :
Based on available data; the classification criter	-
Specific target organ systemic toxicity - repeate	ed exposure :
Based on available data; the classification criter	ia are not met.
Aspiration hazard :	
Based on available data; the classification criter	ia are not met.
Delayed and immediate effects as well as chron	ic effects from short and long-term exposure
No further relevant information available.	
11.2. Information on other hazards	
Other information	
No further relevant information available.	
SECTION 12 : ECOLOGICAL INFORMATION	N
12.1. Toxicity	
12.1.1. Substances	
ETHANOL (CAS: 64-17-5)	
Fish toxicity :	LC50 > 100 mg/l
Crustacean toxicity :	EC50 > 100 mg/l
Algae toxicity :	ECr50 > 100 mg/l
Aquatic plant toxicity :	ECr50 > 100 mg/l
12.1.2. Mixtures	
No aquatic toxicity data available for the mixtur	e.
12.2. Persistence and degradability	
12.2.1. Substances	
ALCOHOLS C12-14, ETHOXYLATED (C.	
Biodegradability :	Rapidly degradable.
ETHANOL (CAS: 64-17-5)	
Biodegradability :	Rapidly degradable.
12.3. Bioaccumulative potential	
No data available.	
12.4. Mobility in soil	
No data available.	
12.5. Results of PBT and vPvB assessment No data available.	
12.6. Endocrine disrupting properties	
No data available.	
12.7. Other adverse effects	
No data available.	

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

14.1. UN number or ID number

1950

14.2. UN proper shipping name UN1950=AEROSOLS, flammable

- 14.3. Transport hazard class(es)
 - Classification :



2.1

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344	E0	2	D
							625			
		-				-	-			_
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
										_
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167	E0	
								A802		
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

The chemical safety assessment has not been carried out for this mixture.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects

Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

- STEL : Short-term exposure limit
- TWA : Time Weighted Averages
- TMP : French Occupational Illness table
- TLV : Threshold Limit Value (exposure)
- AEV : Average Exposure Value.
- ADR : European agreement concerning the international carriage of dangerous goods by Road.
- IMDG : International Maritime Dangerous Goods.
- IATA : International Air Transport Association.
- ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

- PBT: Persistent, bioaccumulable and toxic.
- vPvB : Very persistent, very bioaccumulable.
- SVHC : Substances of very high concern.