

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of

issue: 5/13/2014

Revision date: 11/9/2016

Supersedes: 9/10/2014

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : TECHNO DECAPANT PEINTURE GRAFFITI
Product code : 307121
Product identification : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Paint stripper without methylene chloride

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

IPC
10 quai Malbert - CS 71821
29218 BREST CEDEX 2
02-98-43-45-44 02-98-44-22-53

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Danger
Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP) : P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P403 - Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Extra phrases : For professional use only
Not to be used for any purpose other than the one the product was designed for

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
DIOXOLANNE 1,3	(CAS-No.) 646-06-0 (EC-No.) 211-463-5 (EC Index-No.) 605-017-00-2	60 - 80	Flam. Liq. 2, H225
N-Butane (contenant <0.1% butadiène)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	10 - 20	Flam. Gas 1, H220 Press. Gas (Liq.), H280
	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5 (REACH-no) 01-2119492630-38	5 - 8	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302
NAPHTA 90/160	(CAS-No.) 90989-38-1 (EC-No.) 918-668-5 (REACH-no) 01-2119486136-34	5 - 8	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	5 - 8	Flam. Gas 1, H220 Press. Gas (Liq.), H280
mesitylene, 1,3,5-trimethylbenzene substance with a Community workplace exposure limit	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5	0.5 - 1	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411
Xylène	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	0.1 - 0.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
ethylbenzene substance with a Community workplace exposure limit	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	0.1 - 0.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Specific concentration limits:

Name	Product identifier	Specific concentration limits
mesitylene, 1,3,5-trimethylbenzene	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5	(C >= 25) STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest. Obtain medical attention if breathing difficulty persists.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Wash with plenty of water/.... Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: Obtain medical attention if pain, blinking or redness persists. In case of eye contact, immediately rinse with clean water for 20-30 minutes.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Allow the victim to rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation of vapour can cause breathing difficulties.
Symptoms/effects after skin contact	: mild skin irritation.
Symptoms/effects after eye contact	: Splashes in the eyes may cause irritation and reversible local damage.

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects after ingestion : Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

Advice to physicians: Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Alcohol resistant foam. Dry powder. Carbon dioxide. Chemical powder.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Reactivity in case of fire : Prevent fire fighting water from entering the environment.

5.3. Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions : During a fire, projections ignited aerosol that burst under excessive pressure have to be controlled. To avoid overpressure, cool aerosols with water. Exercise caution when fighting any chemical fire. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Measures to take in the case of crushing or piercing aerosols, causing the leaking of products contained in aerosols. Ventilate area. Do not smoke. Remove ignition sources. Provide local exhaust or general room ventilation. Evacuate and limit access.

6.1.1. For non-emergency personnel

Emergency procedures : Do not touch spilled material. Evacuate area.

6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment. Provide adequate ventilation. Remove all sources of ignition. Avoid contact with skin and eyes. Do not inhale vapour.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Collect the residue by means of a non-combustible absorbent material. Sand. Earth. Vermiculite. Waste mixtures containing butane / propane must not enter drains or sewers where vapors could accumulate and ignite.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Good ventilation of the workplace required. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Not to be used for any purpose other than the one the product was designed for. Do not breathe gas, fumes, vapour or spray. During the handling of a pallet, you have to take all precaution to avoid a start of a n accident perforation of the aerosol by a fork-lift truck. During the load and unloading of the vehicle, you have to take all the precaution to avoid a fall a aerosol. Do not spray tha aerosol neither close nor towards a flame, a white-hot body, an electrical appliance in runing, DO NOT SMOCKING. Container under pressure. Do not drill or burn even after use. Store and handle as though always a serious potential fire/explosion and health hazard exists.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep at temperature not exceeding 50°C. Proper grounding procedures to avoid static electricity should be followed. Use grounded electrical/mechanical equipment.

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- Storage conditions : Recommendations applicable to warehouses and reserves which are stored aerosols. It is recommended to de-normalize aerosols in stock . The " aerosol " or area must be set with a wire mesh of mesh max 5cm, forming a cage or using walls to avoid splashing the aerosols may ignite rest of the stock . Do not smoke.
- To reduce the risk of falling, should position the pallet closest to the ground. If the packages are stacked, it should ensure that those lower layers do not crash (risk of leakage through compression).
- It is recommended :
- Ventilate the premises and not store any sprays near heat sources, including sunlight, sparks and open flames
 - To use the procedure of fire when working . Store in a dry, well ventilated place .

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

N-Butane (contenant <0.1% butadiène) (106-97-8)		
France	Local name	n-Butane
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	800 ppm
France	Note (FR)	Valeurs recommandées/admises
mesitylene, 1,3,5-trimethylbenzene (108-67-8)		
EU	Local name	Mesitylene (Trimethylbenzenes)
EU	IOELV TWA (mg/m ³)	100 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
France	Local name	1,3,5-Triméthylbenzène (Mésit(h)ylène)
France	VME (mg/m ³)	100 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	250 mg/m ³
France	VLE (ppm)	50 ppm
France	Note (FR)	Valeurs réglementaires contraignantes
ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m ³)	442 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	884 mg/m ³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
France	Local name	Ethylbenzène
France	VME (mg/m ³)	88.4 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	402 mg/m ³
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Xylène (1330-20-7)		
France	VME (mg/m ³)	221 mg/m ³
France	VME (ppm)	50 ppm
France	VLE (mg/m ³)	442 mg/m ³
France	VLE (ppm)	100 ppm

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Wear suitable gloves resistant to chemical penetration. Polyvinyl alcohol or nitrile-butyl rubber gloves. Nitrile-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer.

Eye protection:

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Safety glasses with side shields

Skin and body protection:

Skin protection appropriate to the conditions of use should be provided

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter type: A/P2

Other information:

Do not eat, drink or smoke during use. Provide local exhaust or general room ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: milky. light cream.
Odour	: ethereal.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 0 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1 (PA)
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 736 g/l (89%)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

The product is stable at normal handling and storage conditions. Extremely flammable aerosol. Heating may cause a fire or explosion.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Open flame. Heat. Direct sunlight. Sparks. Avoid the build-up of electrostatic charge. Avoid contact with hot surfaces. Remove all sources of ignition.

10.5. Incompatible materials

Strong oxidizers. Aerosol cases in metal, do not bring into contact with oxidize, acids or basis.

10.6. Hazardous decomposition products

No additional information available

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

N-Butane (contenant <0.1% butadiène) (106-97-8)

LC50 inhalation rat (mg/l)	658 mg/l/4h
----------------------------	-------------

(100-51-6)

LD50 oral rat	1230 mg/kg
LD50 oral	1620 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 4.178 mg/l/4h

DIOXOLANNE 1,3 (646-06-0)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

NAPHTA 90/160 (90989-38-1)

LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	12126 mg/kg
LC50 inhalation rat (mg/l)	3523 mg/kg

Skin corrosion/irritation : Not classified
pH: Not applicable

Additional information : Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified
pH: Not applicable

Additional information : Based on available data, the classification criteria are not met

Respiratory or skin sensitisation : Not classified

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-repeated exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

DECAPANT PEINTURE

Product identification	Aerosol
------------------------	---------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Avoid release to the environment.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

N-Butane (contenant <0.1% butadiène) (106-97-8)

LC50 fish 1	24.11 mg/l
EC50 Daphnia 1	14.22 mg/l

(100-51-6)

LC50 fish 1	460 mg/l
EC50 Daphnia 1	360 mg/l

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

(100-51-6)	
EC50 Daphnia 2	230 mg/l
EC50 72h algae (1)	770 mg/l Pseudokirchneriella subcapitata
EC50 96h algae (1)	640 mg/l scenedesmus quadricauda
NOEC chronic algae	310 mg/l Pseudokirchneriella subcapitata

DIOXOLANNE 1,3 (646-06-0)	
LC50 fish 1	95.4 mg/l
EC50 Daphnia 1	1772 mg/l
ErC50 (algae)	877 mg/l
NOEC chronic fish	546.3 mg/l
NOEC chronic crustacea	197.4 mg/l
NOEC chronic algae	877 mg/l

NAPHTA 90/160 (90989-38-1)	
LC50 fish 1	460 mg/l Pimephales promelas (Vairon à grosse tête); 96 h
LC50 fish 2	2.6 mg/l
EC50 Daphnia 1	1 mg/l
EC50 72h algae (1)	2.2 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

N-Butane (contenant <0.1% butadiène) (106-97-8)	
Bioaccumulative potential	Not potentially bioaccumulable.

Propane (74-98-6)	
Bioaccumulative potential	No information available.

(100-51-6)	
Log Pow	11

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations






13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose used or damaged aerosol cans at permitted disposal sites. Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1950	1950	1950	1950	1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 736 g/l (89%)

Other information, restriction and prohibition regulations : Aerosol Generator Directive 75/324/EEC and its adaptations.

15.1.2. National regulations

France

Occupational diseases : RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel
RG 4 BIS - Affections gastro-intestinales provoquées par le benzène, le toluène, les xylènes et tous les produits en renfermant

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
	SDS EU format	Modified	
2.2	S-phrases	Removed	
2.2	R-phrases	Removed	
5.1	Suitable extinguishing media	Modified	
5.2	Explosion hazard	Added	
8.2	Respiratory protection	Modified	
8.2	Hand protection	Modified	
8.2	Appropriate engineering controls	Added	
9.1	Explosive properties	Added	
10.1	Reactivity	Added	
10.2	Chemical stability	Modified	
10.4	Conditions to avoid	Modified	
13.1	Waste disposal recommendations	Modified	

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : Imp. DL4.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

TECHNO DECAPANT PEINTURE GRAFFITI

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product