

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 05/04/2024 Revision date: 17/10/2025 Supersedes version of: 11/06/2024 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : LOFT AMBIANCE ECLAT
Product code : B10901
Product identification : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

[IPC](#)
[10 Quai Malbert](#)
[29200 BREST France](#)
[Tél : +33\(0\)2.98.43.45.44](#)
[Fax : +33 \(0\)2.98.44.22.53](#)
ipc@groupe-ipc.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
Eye Irrit. 2 H319
Full text of hazard classes, H- and EUH-statements: see section 16


Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray. P271 - Use only outdoors or in a well-ventilated area. P403 - Store in a well-ventilated place. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.
Extra phrases	: For professional use only. Not to be used for any purpose other than the one the product was designed for. Seek medical attention if ill effect develops.
Derogation from labelling requirements according to CLP Article 23(c); Annex I Part 1 Section 1.3.3	

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-Butane (contenant <0.1% butadiène) (Propellant gas (Aerosol))	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	40 – 60	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
propane (Propellant gas (Aerosol))	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	20 – 30	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
Isobutane (containing < 0,1 % butadiene) (Propellant gas (Aerosol)) (Note C)(Note U)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	10 – 20	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
ethanol substance with national workplace exposure limit(s) (FR)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	5 – 8	Flam. Liq. 2, H225 Eye Irrit. 2, H319
2-tert-Butylcyclohexylacetate	CAS-No.: 88-41-5 EC-No.: 201-828-7	< 0,1	Aquatic Chronic 2, H411
2-phenylethanol	CAS-No.: 60-12-8 EC-No.: 200-456-2 REACH-no: 01-2119963921-31	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,4-dimethyl-4,4a,5,9b-tetrahydroindeno[1,2-d]-1,3-dioxin	CAS-No.: 27606-09-3 EC-No.: 248-561-2	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Aquatic Chronic 3, H412
(Z)-3-hexenyl salicylate	CAS-No.: 65405-77-8 EC-No.: 265-745-8 REACH-no: 01-2119987320-37	< 0,1	Aquatic Acute 1, H400
5-cyclohexadecen-1-one	CAS-No.: 37609-25-9 EC-No.: 253-568-9	< 0,1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-methylpropan-2-ol substance with national workplace exposure limit(s) (FR)	CAS-No.: 75-65-0 EC-No.: 200-889-7 EC Index-No.: 603-005-00-1 REACH-no: 01-2119444321-51	< 0,1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Eye Irrit. 2, H319 STOT SE 3, H335

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
ethanol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	(50 ≤ C < 100) Eye Irrit. 2; H319

Comments : Calculation of aerosol labeling excluding gas

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Allow the victim to rest.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after ingestion : None under normal conditions. Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Reactivity in case of fire : Prevent fire fighting water from entering the environment.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. During a fire, projections ignited aerosol that burst under excessive pressure have to be controlled. To avoid overpressure, cool aerosols with water. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. Measures to take in the case of crushing or piercing aerosols, causing the leaking of products contained in aerosols. Ventilate area. Do not smoke. Remove ignition sources. Provide local exhaust or general room ventilation. Evacuate and limit access. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not touch spilled material. Evacuate area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so. Provide adequate ventilation. Do not inhale vapour.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Mechanically recover the product. Clean spills promptly. Collect the residue by means of a non-combustible absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling

- : Not expected to present a significant hazard under anticipated conditions of normal use.
- : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Not to be used for any purpose other than the one the product was designed for. Do not breathe gas, fumes, vapour or spray. During the handling of a pallet, you have to take all precaution to avoid a start of a n accident perforation of the aerosol by a fork-lift truck. During the load and unloading of the vehicle, you have to take all the precaution to avoid a fall a aerosol. Do not spray tha aerosol neither close nor towards a flame, a white-hot body, an electrical appliance in runing, DO NOT SMOCKING. Container under pressure. Do not drill or burn even after use. Store and handle as though always a serious potential fire/explosion and health hazard exists.

Hygiene measures

- : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Storage conditions

- : Keep in a cool, well-ventilated place away from heat. Proper grounding procedures to avoid static electricity should be followed. Use grounded electrical/mechanical equipment.
- : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Recommendations applicable to warehouses and reserves which are stored aerosols. It is recommended to de-normalize aerosols in stock . The " aerosol " or area must be set with a wire mesh of mesh max 5cm, forming a cage or using walls to avoid splashing the aerosols may ignite rest of the stock . Do not smoke.

To reduce the risk of falling, should position the pallet closest to the ground. If the packages are stacked, it should ensure that those lower layers do not crash (risk of leakage through compression).

It is recommended :

- Ventilate the premises and not store any sprays near heat sources, including sunlight, sparks and open flames

- To use the procedure of fire when working . Store in a dry, well ventilated place .

Packaging materials

- : Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

N-Butane (contenant <0.1% butadiène) (106-97-8)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1450 mg/m³
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m³

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

N-Butane (contenant <0.1% butadiène) (106-97-8)

750 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Skin protection appropriate to the conditions of use should be provided

Hand protection:

Protective gloves. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0,83 (PA)
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 98 %

9.2.2. Other safety characteristics

VOC content : 98,2 % (554.7 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Extremely high or low temperatures. Do not expose to temperatures exceeding 50 °C/ 122 °F.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

ethanol (64-17-5)	
LD50 oral	10470 mg/kg
LD50 dermal	15800 mg/kg
LC50 Inhalation - Rat	50000 mg/m ³

2-methylpropan-2-ol (75-65-0)	
LD50 dermal	> 2000 mg/kg

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)

2-methylpropan-2-ol (75-65-0)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

LOFT AMBIANCE ECLAT	
Product identification	Aerosol

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

ethanol (64-17-5)	
LC50 - Fish [1]	11200 mg/l
LC50 - Fish [2]	13000 mg/l
EC50 - Crustacea [1]	12340 mg/l
EC50 72h - Algae [1]	275 mg/l

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methylpropan-2-ol (75-65-0)

EC50 - Crustacea [1]	933 mg/l
----------------------	----------

12.2. Persistence and degradability

LOFT AMBIANCE ECLAT

Persistence and degradability	Not established.
-------------------------------	------------------

N-Butane (contenant <0.1% butadiène) (106-97-8)

Persistence and degradability	Half-life time in water: <2.6 d Half-life time in air: 3.2 d.
-------------------------------	--

propane (74-98-6)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Biodegradation	< 60 % 28d
----------------	------------

Isobutane (containing < 0,1 % butadiene) (75-28-5)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

ethanol (64-17-5)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

2-methylpropan-2-ol (75-65-0)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Biodegradation	99 %
----------------	------

2-tert-Butylcyclohexylacetate (88-41-5)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

2-phenylethanol (60-12-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

2,4-dimethyl-4,4a,5,9b-tetrahydroindeno[1,2-d]-1,3-dioxin (27606-09-3)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

(Z)-3-hexenyl salicylate (65405-77-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

5-cyclohexadecen-1-one (37609-25-9)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

N-Butane (contenant <0.1% butadiène) (106-97-8)

Bioaccumulative potential	Not potentially bioaccumulable.
---------------------------	---------------------------------

propane (74-98-6)

Bioaccumulative potential	No information available.
---------------------------	---------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations. Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Additional information	: Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations	: Aerosol Generator Directive 75/324/EEC and its adaptations.
--	---

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	LOFT AMBIANCE ECLAT ; ethanol ; 2-methylpropan-2-ol
3(b)	LOFT AMBIANCE ECLAT ; ethanol ; 2-methylpropan-2-ol
3(c)	2-tert-Butylcyclohexylacetate

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 98,2 % (554.7 g/l)

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
1.1	Name	Added
1.1	UFI on SDS 1.1	Modified
1.2	Main use category	Modified
2	Derogation/exemption from labelling	Added
2.2	Extra phrases	Modified
4	Self protection of the first-aider	Added
4.2	Symptoms/effects after inhalation	Modified
9	VOC content	Modified

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
9	Flash point	Removed
9	Relative density	Modified
12.2	Persistence and degradability	Added
14	Packing instructions (ADR)	Modified
15.1	REACH Annex XVII	Modified
16	Abbreviations and acronyms	Modified

Abbreviations and acronyms:	
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

LOFT AMBIANCE ECLAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.